



Description

- Choice for shelf liner; flexible, tough, and fairly hard
- Low cost
- Made of a modified polyethylene; offers excellent chemical resistance
- Should not be used at solder stations

Specifications

Rs: 1×10^3 to $< 1 \times 10^6$ ohms tested per IEC 61340-2-3 meets EN 61340-5-1

Rg: 1×10^3 to $< 1 \times 10^6$ ohms tested per IEC 61340-2-3 meets EN 61340-5-1

Thickness: 1.5mm

Weight: 1.4 kg/m²

Colour: black

Item	Description
VER-27089	1.5mm x 0.9m x 0.54m, 4 x 10mm studs
VER-26945	1.5mm x 1.2m x 0.54m, 4 x 10mm studs
VER-26946	1.5mm x 1.1m x 2.4m, no studs

"All working surfaces and storage racks on which unprotected ESDS [ESD sensitive items] may be placed shall be capable of being connected to EPA ground and shall have a point-to-point resistance and resistance to EPA ground in accordance with table 1 (Rp greater or equal to 1×10^4 , less than or equal to 1×10^9 ohms, and Rg greater or equal to 7.5×10^5 to less than or equal to 1×10^9 ohms) and shall contain a groundable point."

*Colour and texture may vary between lots and mills

Made in the United Kingdom with globally sourced materials

If not otherwise noted, tolerance +/- 10%

Vermason

EVA Bench Matting and Shelf Lining

VERMASON LTD.
 UNIT C, 4TH DIMENSION, FOURTH AVENUE, LETCHWORTH,
 HERTS, SG6 2TD UK
 PHONE: +44 (0) 1462-672005, FAX: +44 (0) 1462-670440
 E-MAIL: Service@Vermason.co.uk, INTERNET: Vermason.co.uk

Drawing Number
VER-27089

DATE:
 November
 2015