## Product data sheet Characteristics

## ZCKJ9

Limit switch body, Limit switches XC Standard, ZCKJ, fixed, w/o display, 2NC, snap action, Pg13



# Main

Range of Product	Telemecanique Limit switches XC Standard	
Series name	Standard format	
Product or Component Type	Limit switch body	
Device short name	ZCKJ	
Body type	Fixed	
Product Compatibility	XCKJ	
Associated head	ZCKE66 ZCKE65 ZCKE629 ZCKE61 ZCKE619 ZCKE64 ZCKE05 ZCKE62 ZCKE62 ZCKE63 ZCKE63 ZCKE08 ZCKE23 ZCKE21 ZCKE06 ZCKE66	
Body Material	Metal	
Cable entry	1 entry tapped for Pg 13.5 cable gland	
Number of poles	2	
Contacts type and composition	2 NC	
Contact operation	Snap action	
Number of steps	1 1 position	
Contacts material	Silver plated contacts	

#### Complementary

Complementary	
Local display	Without
Electrical connection	Screw-clamp terminals 1 x 0.342 x 1.5 mm <sup>2</sup>
Positive opening	With
Minimum actuation speed	0.01 m/min
[le] rated operational current	3 A 240 V, AC-15, A300 EN/IEC 60947-5-1 appendix A 0.27 A 250 V, DC-13, Q300 EN/IEC 60947-5-1 appendix A
[Ithe] conventional enclosed thermal current	10 A
[Ui] rated insulation voltage	500 V 3)IEC 60947-1 contact block 300 VCSA C22.2 No 14 contact block 300 VUL 508 contact block
Maximum resistance across terminals	0.25 mOhm IEC 60255-7 category 3
[Uimp] rated impulse withstand voltage	4 KV IEC 60664 4 kV IEC 60947-1
Short-circuit protection	6 A cartridge fuse gG
Electrical durability	5000000 Cycles, DC-13 120 V, 1 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 5000000 Cycles, DC-13 24 V, 3 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 5000000 cycles, DC-13 48 V, 2 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C
Width	1.57 in (40 mm)
Height	3.03 in (77 mm)
Depth	1.73 in (44 mm)

Net Weight	0.68 lb(US) (0.31 kg)
Terminals description ISO n°1	(21-22)NC (33-34)NO
	(13-14)NO
Environment	
IP Degree of Protection	IP66
IK Degree of Protection	IK07
Ambient air temperature for operation	-13158 °F (-2570 °C) standard environment

-40...158 °F (-40...70 °C)

Standard environment

#### Ordering and shipping details

Ambient Air Temperature for Storage

Environmental characteristic

22411-LIMIT SWITCHES,IEC,XCKJ
Т
3389110619324
1
10.02 oz (284.0 g)
No
FR

#### **Packing Units**

1 doking office	
Unit Type of Package 1	PCE
Package 1 Height	1.57 in (4 cm)
Package 1 width	1.81 in (4.6 cm)
Package 1 Length	3.31 in (8.4 cm)
Unit Type of Package 2	S02
Number of Units in Package 2	24
Package 2 Weight	15.71 lb(US) (7.128 kg)
Package 2 Height	5.91 in (15 cm)
Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)

#### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS  Declaration
Mercury free	Yes
RoHS exemption information	€Yes
Environmental Disclosure	Product Environmental Profile

### Contractual warranty

101	40
Warranty	18 months