

# HSK-MINI Metric 1.106.1001.50

Liquid tight strain relief fittings for the smallest cable OD

<b>cable diameter</b>	4 – 6 mm
<b>Height</b>	14 mm
<b>Male thread</b>	M 10 x 1,5
<b>Material</b>	nickel-plated brass
<b>O-Ring</b>	NBR/ FKM
<b>Operating-Temperature</b>	-20 – 100 °C
<b>Protection category</b>	IP 68
<b>Seal</b>	NBR/ TPE/ FKM
<b>Seal ring</b>	TPE
<b>Thread Length</b>	6 mm
<b>Wrench size</b>	12 mm

[SUPPORT](#)

[DOWNLOAD 3D DATA](#)

Certificates [i](#)

[ADD TO WATCHLIST](#)

[PRINT](#)

Advice:

- // Other sealing material e.g. Silicone upon request
- // Other thread pitches on request
- // Stainless steel 1.4404 on request

ELECTRIC COMPONENTS

- Circular Connectors
- Industrial Cable Glands
- Industrial Ex Cable Glands
- "Hazardous Areas" Cable Glands
- Conduit Systems
- Customized Projects

HEATING EQUIPMENT

- Problem Fixer
- Fittings
- Designtechnik
- Boiler Connection
- Underfloor Heating
- Accessories, Spare Parts, Tools

INFORMATION

- News
- Imprint
- Privacy Policy
- GTC

NEWSLETTER

[SUBSCRIBE TO NEWSLETTER](#)

[OK](#)