

Recommended PCB Layout
(Bottom View)

Materials and Finish

Housing: PBT Thermoplastic
15% Glass Filled, Black Color
UL 94V-0 Rated

Terminals:

- Pin #1: Brass, Nickel Plated
- Pin #5 & Pin #2: Phosphor Bronze, Matte Tin Plated
- Pin #3 & Pin #4: Brass, Matte Tin Plated

Bushing: Brass, Nickel Plated

Electrical Characteristics

- Rated Voltage: DC 24 V
- Rated Current: 3.0 A
- Contact Resistance:
Before Test: 50mohms Max.
After Durability Test: 100 mohms Max.

Insulation Resistance:
More Than 100 Megohms
At 500V DC

Dielectric Strength:
500V AC RMS for 1 Minute

Operating Temp: -25°C to +85°C

Mechanical Characteristics

- Insertion Force: 0.3kg - 3.0kg
- Extraction Force: 0.3kg - 3.0kg
- Durability: 5000 Mating Cycles Min.

RoHS COMPLIANT

Tolerances


X.X ± 0.3
X.XX ± 0.15
Unless Stated
Otherwise

REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A1	9/6/05	New Drawing	R. Aguirre	H. MA	R. Aguirre	07/13/05
A2	11/8/06	ECO #06-046	R. Aguirre	H. MA		
A3	07/14/11	ECO #11-033	S. Vien	P. DalCanto		
A4	08/14/18	Update Address	D. Shehan	N/A		
A5	04/22/19	ECO #19-035	C. Kelleher	D. Shehan		

STX-3100-5NB

3.5mm Stereo Jack, RoHS Compliant

One Single Throw Double Pole Switch, with Back



UNITS
mm