


REV.0
DCO 143870

COIL: @ 25°C	
RESISTANCE	1600 OHMS ±10%
NOMINAL VOLTAGE	18.0 VDC
MUST OPERATE	9.8 VDC
MUST RELEASE	6.0 VDC MAX., 0.92 VDC MIN.

ENVIRONMENT:	
VIBRATION	10 Hz TO 3000 Hz @ 30 g's
SHOCK	75 g's 6 MS. DURATION
TEMPERATURE	-65 °C TO +125 °C

NOTES:	OPERATE TIME 4.0 MS MAX.
	RELEASE TIME 2.5 MS MAX.
	CONTACT STABILIZATION TIME 2.5 MS MAX.

CUSTOMER DATA SHEET



CONTACT RATING: LOW LEVEL TO 1 AMP
28 VDC RESISTIVE 100,000 OPERATIONS MIN.

DR. B.D. 22APR04

CK. JERRY C. 4/22/04

CII Technologies™
advanced control electronic solutions

CUST. QPL
CUST. NO. M39016/41-048M REV.

"JMGS" RELAY

JMGSP-18M

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[JMGSP-18M](#)