

Jul. 1. 2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.  
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE			
△				.	△				.			
△				.	△				.			
<b>APPLICABLE STANDARD</b>												
<b>RATING</b>	OPERATING TEMPERATURE RANGE	-35 °C TO +85 °C (NOTE1)			STORAGE TEMPERATURE RANGE	-10 °C TO +60 °C						
	VOLTAGE	250 V AC			APPLICABLE CONTACT							
	CURRENT	3 A			APPLICABLE CONNECTOR							
					APPLICABLE CABLE							
<b>SPECIFICATIONS</b>												
<b>ITEM</b>	<b>TEST METHOD</b>				<b>REQUIREMENTS</b>				<b>Q</b>	<b>T</b>	<b>A</b>	<b>T</b>
<b>CONSTRUCTION</b>												
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.				ACCORDING TO DRAWING.				○	○		
MARKING	CONFIRMED VISUALLY.								○	○		
<b>ELECTRICAL CHARACTERISTICS</b>												
CONTACT RESISTANCE	100 mA (DC OR 1000 Hz).				30 mΩ MAX.				○	—		
CONTACT RESISTANCE MILLIVOLT LEVEL METHOD.	20 mV MAX. mA (DC OR 1000 Hz).				mΩ MAX.				—	—		
INSULATION RESISTANCE	500 V DC				1000 MΩ MIN.				○	—		
VOLTAGE PROOF	650 V AC FOR 1 min				NO FLASHOVER OR BREAKDOWN.				○	—		
<b>MECHANICAL CHARACTERISTICS</b>												
CONTACT INSERTION AND EXTRACTION FORCES	BY STEEL GAUGE.				INSERTION FORCE N MAX. EXTRACTION FORCE N MIN.				—	—		
INSERTION AND WITHDRAWAL FORCES	MEASURED BY APPLICABLE CONNECTOR.				INSERTION FORCE N MAX. EXTRACTION FORCE N MIN.				—	—		
MECHANICAL OPERATION	≥ 20 TIMES INSERTIONS AND EXTRACTIONS				① CONTACT RESISTANCE: 30 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				○	—		
VIBRATION	FREQUENCY 10 TO 55 Hz. SINGLE AMPLITUDE 0.75 mm. — m/s <sup>2</sup> AT 2 h FOR 3 DIRECTIONS.				① NO ELECTRICAL DISCONTINUITY OF PARTS. ② CONTACT RESISTANCE: — mΩ MAX. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				○	—		
SHOCK	490 m/s <sup>2</sup> DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.				① NO ELECTRICAL DISCONTINUITY OF PARTS. ② CONTACT RESISTANCE: — mΩ MAX. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				○	—		
<b>ENVIRONMENTAL CHARACTERISTICS</b>												
DAMP HEAT (STEADY STATE)	EXPOSED AT 40±2 °C, 90~95%, 96 h.				① CONTACT RESISTANCE: 30 mΩ MAX. ② INSULATION RESISTANCE: 1000 MΩ MIN. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				○	—		
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55 → -5~35 → +85 → 5~35 °C TIME 30 → 5 → 30 → 5 min UNDER 5 CYCLES.				① CONTACT RESISTANCE: 30 mΩ MAX. ② INSULATION RESISTANCE: 1000 MΩ. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				○	—		
RESISTANCE TO SOLDERING HEAT	SOLDER TEMPERATURE, IMMERSION, DURATION, °C FOR s.				NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.				—	—		
SOLDERABILITY	SOLDERED AT SOLDER TEMPERATURE, FOR IMMERSION DURATION, °C s.				A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMersed.				—	—		
REMARKS NOTE1 INCLUDE THE TEMPERATURE RISING BY CURRENT. Unless otherwise specified, refer to MIL-STD-1344.					DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED			
					R. Sasaki	M. Tanaka	J. Oma	H. Yamamoto				
					'95.10.12	'95.10.13	'95.10.17	'95.10.23				
Note Q T: Qualification Test    A T: Assurance Test    ○: Applicable Test												
<b>HRS</b> HIROSE ELECTRIC CO., LTD.					<b>SPECIFICATION SHEET</b>			PART NO. DF1BA-※EP-2.5RC				
CODE NO. (OLD) CL			DRAWING NO. ELC4-160595			CODE NO. CL			CODE NO. SHALL BE IN ACCORDANCE WITH TABLE.		1/1	

TO  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_