XZCPV0566L10



Main

Accessory / separate part category	Cabling accessory
Accessory / separate part type	Pre-wired connectors
Series name	General purpose

Complementary

Electrical connection M8, 3 pins straight female connector Cable connector fixing Screw-on Collar material Metal Status LED Without Cable length 32.81 ft (10 m) Cable outer diameter 0.18 in (4.6 mm) Cable composition 3 x 0.25 mm² Wire insulation material PVC System Voltage 60 V AC 75 V DC Line Rated Current 3 A Contact resistance 5000 μOhm Insulating resistance 1 GΩ Product weight 0.7 lb(US) (0.316 kg)	oompromornary		
Collar material Metal Status LED Without Cable length 32.81 ft (10 m) Cable outer diameter 0.18 in (4.6 mm) Cable composition $3 \times 0.25 \text{ mm}^2$ Wire insulation material PVC System Voltage 60 V AC 75 V DC Line Rated Current 3 A Contact resistance $5000 \mu\text{Ohm}$ Insulating resistance $1 \text{ G}\Omega$	Electrical connection	M8, 3 pins straight female connector	
Status LED Without Cable length 32.81 ft (10 m) Cable outer diameter 0.18 in (4.6 mm) Cable composition 3 x 0.25 mm² Wire insulation material PVC System Voltage 60 V AC 75 V DC Line Rated Current 3 A Contact resistance 5000 μOhm Insulating resistance 1 GΩ	Cable connector fixing	Screw-on	
Cable length $32.81 \text{ ft } (10 \text{ m})$ Cable outer diameter $0.18 \text{ in } (4.6 \text{ mm})$ Cable composition $3 \times 0.25 \text{ mm}^2$ Wire insulation material PVC System Voltage 60 V AC 75 V DC Line Rated Current 3 A Contact resistance $5000 \mu\text{Ohm}$ Insulating resistance $1 \text{ G}\Omega$	Collar material	Metal	
Cable outer diameter $0.18 \text{ in } (4.6 \text{ mm})$ Cable composition $3 \times 0.25 \text{ mm}^2$ Wire insulation material PVC System Voltage 60 V AC 75 V DC Line Rated Current 3 A Contact resistance $5000 \mu\text{Ohm}$ Insulating resistance $1 \text{ G}\Omega$	Status LED	Without	
Cable composition $3 \times 0.25 \text{ mm}^2$ Wire insulation material PVC System Voltage 60 V AC 75 V DC Line Rated Current 3 A Contact resistance $5000 \mu\text{Ohm}$ Insulating resistance $1 \text{ G}\Omega$	Cable length	32.81 ft (10 m)	
Wire insulation material PVC System Voltage 60 V AC 75 V DC Line Rated Current 3 A Contact resistance $5000 \mu\text{Ohm}$ Insulating resistance $1 \text{ G}\Omega$	Cable outer diameter	0.18 in (4.6 mm)	
	Cable composition	3 x 0.25 mm²	
75 V DC Line Rated Current 3 A Contact resistance 5000 μOhm Insulating resistance 1 GΩ	Wire insulation material	PVC	
Contact resistance 5000 μOhm Insulating resistance 1 GΩ	System Voltage		
Insulating resistance $1 G\Omega$	Line Rated Current	3 A	
	Contact resistance	5000 μOhm	
Product weight 0.7 lb/LIS\ (0.316 kg)	Insulating resistance	1 GΩ	
1.7 bd det weight 0.7 b (0.5 to kg)	Product weight	0.7 lb(US) (0.316 kg)	

Environment

IP degree of protection	IP65 IP67	## Per page
product certifications	CULus	
ambient air temperature for operation	-13176 °F (-2580 °C) (static)	<u> </u>
ambient air temperature for storage	-13176 °F (-2580 °C)	


Offer Sustainability

Warranty period

Offer Sustainability			
Not Green Premium product	Not Green Premium product		
Compliant - since 1201 - Schneider Electric declaration of conformity	Compliant - since 1201 - Schneider Electric declaration of conformity		
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:		
Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and	Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and		
Di-isodecyl phthalate (DIDP), which is known to the StateDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth of California to cause birth defects or other reproductive harm. harm.			
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov		
Control de la constant			
Contractual warranty			

18 months


Dimensions



L: Lenght of cable

Connections and Schemes

Connector



BU : Blue
BN : Brown
BK : Black

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric: XZCPV0566L10