



Part No	Pin	A	B	Part No	Pin	A	B
WAFER-0.8-2PLB	2	0.80	3.85	WAFER-0.8-14PLB	14	10.40	13.45
WAFER-0.8-3PLB	3	1.60	4.65	WAFER-0.8-15PLB	15	11.20	14.25
WAFER-0.8-4PLB	4	2.40	5.45	WAFER-0.8-16PLB	16	12.00	15.05
WAFER-0.8-5PLB	5	3.20	6.25	WAFER-0.8-17PLB	17	12.80	15.85
WAFER-0.8-6PLB	6	4.00	7.05	WAFER-0.8-18PLB	18	13.60	16.65
WAFER-0.8-7PLB	7	4.80	7.85	WAFER-0.8-19PLB	19	14.40	17.45
WAFER-0.8-8PLB	8	5.60	8.65	WAFER-0.8-20PLB	20	15.20	18.25
WAFER-0.8-9PLB	9	6.40	9.45	WAFER-0.8-21PLB	21	16.00	19.05
WAFER-0.8-10PLB	10	7.20	10.25	WAFER-0.8-22PLB	22	16.80	19.85
WAFER-0.8-11PLB	11	8.00	11.05	WAFER-0.8-23PLB	23	17.60	20.65
WAFER-0.8-12PLB	12	8.80	11.85	WAFER-0.8-24PLB	24	18.40	21.45
WAFER-0.8-13PLB	13	9.60	12.65				

NOTES:

- 1.BASE: LCP
- 2.PIN: Brass
- 3.Solder Tab: Brass

SPECIFICATIONS:

- 1.Spacing: 0.8
- 2.Voltage Rating: 30V AC DC
- 3.Current Rating: 0.5A AC DC
- 4.Insulation Resistance: 100MΩ Min
- 5.Contact Resistance: 20mΩ Max
- 6.Withstanding voltage: 200V AC 1/Minute
- 7.Temperatuer Range: -25℃ ~+ 85℃

MANUFACTURE DWG			东莞市讯普电子科技有限公司 DongGuan XunPu Electronics Co.,Ltd	
UNLESS OTHERWISE SPECIFIED TOLERANCES			TITLE: WAFER 0.8 立贴	
DECIMALS:	ANGLES:		PAR	WAFER-0.8-NPLB
X.:±0.2	X'.:±5°		DWN	
.X:±0.1	X.X':±3°		CHKD	
.XX:±0.05	X.XX':±1°		APVD	
CUSTOMER COPY		SCALE1:1	UNIT:MM	
		SIZE:A4	SHEET:1F1	REV:A