



SPECIFICATIONS

- 1、Current Rating: 3A AC, DC
- 2、Voltage Rating: 250V AC, DC
- 3、Temperatuer Range: -25℃~+85℃
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 1000MΩ Min
- 6、Withstanding Voltang: 800V AC/minute
- 7、Material: Wafer Nylon46, UL94V-0
PIN Brass Tin-plated

Circuit	Part NO.	Dimensions mm	
		A	B
2	HC-SPH-2x2A	2.00	6.00
3	HC-SPH-2x3A	4.00	8.00
4	HC-SPH-2x4A	6.00	10.00
5	HC-SPH-2x5A	8.00	12.00
6	HC-SPH-2x6A	10.00	14.00
7	HC-SPH-2x7A	12.00	16.00
8	HC-SPH-2x8A	14.00	18.00
9	HC-SPH-2x9A	16.00	20.00
10	HC-SPH-2x10A	18.00	22.00
11	HC-SPH-2x11A	20.00	24.00
12	HC-SPH-2x12A	22.00	26.00

PCB LAYOUT

		GENEERL TOLERANCE		制图 DRAWING	深圳市华灿天禄电子有限公司 ShenzhenhuacantianluELECTRONICS CO.,LTD			
		DIM	TOL	审核 CHECK				
		X.X	±0.30	批准 APPROVAL	产品名称 TITLE	双排直针	版本 REV.	A
		X.XX	±0.20	投影 Projection	产品料号 PART NO.	HC-SPH-2xNA	单位 UNITS	mm
1	初版发行	X.XXX	±0.10		材料 MATERIAL			
序号 No.	变更内容 MODIFY CONTENT	日期 MODIFY DATE	Angle	±3.0°	页次 SHEET			
					1/1			