

PRODUCTS

- Rocker switches
- Pushbutton switches
- Toggle switches
- Slide switches
- Rotary switches
- Foot switches
- Tact and key switches
- Snap-action switches**
- Micro-signal switches
- ECO switches
- Sensors
- Systems and modules
- Accessories
- General information
- Catalog request / download

[PRODUCTS](#) ▶ [SNAP-ACTION SWITCHES](#)

Snap-action switches

SERIES 1022 - SNAP-ACTION SWITCHES IP 67 - TO 4 A 12 V DC

[Show next product ▶](#)

1022.0101

[Drawing](#)


Similar to original product

[→ Print data sheet](#)

Product number	1022.0101
Miscellaneous	pin right 5 long
Switching function	Changeover switch (SPDT momentary)
Number of poles	1-pole
connections	Cable
Mechanical life endurance	10E4
Rating IEC	2 A 24 V DC 10E4 4 A 12 V DC 10E4
Contact resistance (new condition)	< 100 (1 A 12 V DC) mOhm
Insulation resistance (new condition)	> 100 (500 V DC) MOhm
Proof tracking	250 PTI
Protection type	Connection IP 67
Ambient temperature	-40 °C ... +85 °C
Flammability	UL 94 V-2
Actuators and additional actuators	POM, standard actuator, silicone rubber
Housing description	PBTP
Contact material	Au
Contact distance	< 3 mm
Operating force	< 2.5 N
Bounce time	< 5 ms
Difference travel max.	0.6 mm
Free position (FP) max.	12 mm
Operating position (OP)	10.6 ±0.4 mm
Permissible total travel position	9.5 mm