


**SPECIFICATION**

1. Rating : DC 30V 0.5A;
2. Contact resistance:  $\leq 0.03\Omega$ ;
3. Insulation resistance:  $\geq 100M\Omega$  (DC250V);
4. Withstand voltage: 500VAC ;
5. Insertion and extraction force: 3-25N;
6. life test: 5,000 cycles.

**SCHEMATIC**



						容许公差 GENERAL TOLERANCE		深圳市金航标电子有限公司		www.kinghelm.com.cn	
6	COVER	PA66/PBT	1			X. X	$\pm 0.1$	KH-PJ-316		0755-28190160	
5	HOUSING	PA66/PBT	1			X. XX	$\pm 0.05$	型号: Model: 耳机插座 PJ-316			
4	AXIS SUPPORT	H59 BRASS	1	Ni-Plating	修正 REVISION	X. XXX	$\pm 0.005$				
3	CURVE PIECE	H62 BRASS	1	Cu-Sn-Plating	绘制 DRAWN 15-6/12	角度公差 ANGLE TOLERANCE		料号: Part Number:			
2	SPRING PIECE	65Mn STEEL	1	Cu-Sb-Plating	设计 DES' D 15-6/12	X. °	$\pm 5.0^\circ$				
1	FLAT PIECE	H62 BRASS	1	Cu-Sn-Plating	校对 CHK' D 15-6/12	X. X°	$\pm 3.0^\circ$	单位 UNIT	张数 SHEET	比例 SCALE	版本 REV
序号	名称	材料	数量	镀层/颜色	核准 APP' D 15-6/12	X. XX°	$\pm 1.0^\circ$	mm	1/1	4:1	A