



PRINT

Liquidtight Flexible Cord & Cable Fittings

T&B Catalog Number: 2270
UPC Number: 78621002270
Status: Active

Description:

1/2 in. 90 degree malleable iron liquidtight strain relief cord connector, cord range-.450-.560.

ROHS

CAD

SUBMITTAL PACKAGE

Where To Buy

Enter Zip Code:

Enter Quantity:

Application

- Suitable for use in hazardous locations where general purpose equipment is specifically permitted by NEC 501-4(b).
- Meets Coast Guard CG293

General

Material: Malleable Iron

Dimension Information

Hub Size (inches)	1/2
Dimension A (inches)	1 5/32
Dimension B (inches)	1 23/32
Dimension C (inches)	5/8
Cord Range (inches)	.450-.560

Specifications

Temperature Rating: 105 C

Packaging

Inner Package	25
Outer Package	50
Package Height	6.9
Package Length	10.9
Package Width	5.1
T&B Sold in UOM	Each
T&B Weight Per UOM	25.5 lbs. per 100

Application Support

- [Product Overview](#) [Click Here](#)
- [Specifications](#) [Click Here](#)
- [Portable Cord Selection Table](#) [Click Here](#)

Notes

- Suitable for use in hazardous locations where general purpose equipment is specifically permitted by NEC 501-4(b).

Certifications

RoHS Compliance: Yes [Generate Compliance Certificate](#)

Certifications



File Nbr:
E 13938