



Figure similar

SIMATIC ET 200MP. PROFINET IO-DEVICE INTERFACEMODULE IM 155-5 PN ST FOR ET 200MP ELEKTRONIKMODULES; UP TO 12 IO-MODULES WITHOUT ADDITIONAL PS; UP TO 30 IO- MODULES WITH ADDITIONONAL PS SHARED DEVICE; MRP; IRT >=0.25MS; ISOCHRONICITY FW-UPDATE; I&M0...3; FSU WITH 500MS

General information	
Product type designation	IM 155-5 PN ST
HW functional status	From FS01
Firmware version	V4.1.0
Vendor identification (VendorID)	0x002A
Device identifier (DeviceID)	0X0312
Product function	
<ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>	Yes; I&M0 to I&M3
<ul style="list-style-type: none"> <li>Module swapping during operation (hot swapping)</li> </ul>	No
<ul style="list-style-type: none"> <li>Isochronous mode</li> </ul>	Yes
Engineering with	
<ul style="list-style-type: none"> <li>STEP 7 TIA Portal configurable/integrated from version</li> </ul>	V14 or higher with HSP 0223 / integrated with V15 or higher
<ul style="list-style-type: none"> <li>STEP 7 configurable/integrated from version</li> </ul>	GSDML V2.32
<ul style="list-style-type: none"> <li>PROFINET from GSD version/GSD revision</li> </ul>	V2.3 / -
Configuration control	
via user data	No
via dataset	Yes
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Short-circuit protection	Yes
Mains buffering	
<ul style="list-style-type: none"> <li>Mains/voltage failure stored energy time</li> </ul>	10 ms
Input current	
Current consumption (rated value)	0.2 A
Current consumption, max.	1.2 A
Inrush current, max.	9 A
$I^2t$	0.09 A <sup>2</sup> ·s
Power	
Infeed power to the backplane bus	14 W
Power available from the backplane bus	2.3 W
Power loss	
Power loss, typ.	4.5 W
Address area	
Address space per module	
<ul style="list-style-type: none"> <li>Address space per module, max.</li> </ul>	256 byte; per input / output
Address space per station	

• Address space per station, max.	512 byte; per input / output
<b>Hardware configuration</b>	
Integrated power supply	Yes
System power supply can be plugged in to left of IM	Yes
Number of permissible power segments	3
<b>Rack</b>	
• Modules per rack, max.	30; I/O modules
<b>Interfaces</b>	
Number of PROFINET interfaces	1
<b>1. Interface</b>	
<b>Interface types</b>	
• RJ 45 (Ethernet)	Yes
• Number of ports	2
• integrated switch	Yes
<b>Protocols</b>	
• PROFINET IO Device	Yes
• Open IE communication	Yes
• Media redundancy	Yes; PROFINET MRP
<b>PROFINET IO Device</b>	
<b>Services</b>	
— IRT	Yes
— PROFIenergy	No
— Prioritized startup	Yes
— Shared device	Yes
— Number of IO Controllers with shared device, max.	2
<b>Interface types</b>	
<b>RJ 45 (Ethernet)</b>	
• Transmission procedure	PROFINET with 100 Mbit/s full duplex (100BASE-TX)
• 100 Mbps	Yes
• Autonegotiation	Yes
• Autocrossing	Yes
<b>Protocols</b>	
<b>Redundancy mode</b>	
• PROFINET system redundancy (S2)	No
• PROFINET system redundancy (R1)	No
<b>Media redundancy</b>	
— MRP	Yes
— MRPD	No
<b>Open IE communication</b>	
• TCP/IP	Yes
• SNMP	Yes
• LLDP	Yes
<b>Isochronous mode</b>	
Equidistance	Yes
shortest clock pulse	250 µs
max. cycle	4 ms
<b>Interrupts/diagnostics/status information</b>	
Status indicator	Yes
Alarms	Yes
Diagnostics function	Yes
<b>Diagnostics indication LED</b>	
• RUN LED	Yes; green LED
• ERROR LED	Yes; red LED
• MAINT LED	Yes; Yellow LED
• Connection display LINK TX/RX	Yes; 2x green-yellow LEDs
<b>Potential separation</b>	
between backplane bus and electronics	No
between PROFINET and all other circuits	Yes
between supply and all other circuits	No
<b>Isolation</b>	

Isolation tested with	707 V DC (type test)
<b>Ambient conditions</b>	
Ambient temperature during operation	
<ul style="list-style-type: none"> <li>horizontal installation, min.</li> <li>horizontal installation, max.</li> <li>vertical installation, min.</li> <li>vertical installation, max.</li> </ul>	<ul style="list-style-type: none"> <li>-25 °C; From FS03</li> <li>60 °C</li> <li>-25 °C; From FS03</li> <li>40 °C</li> </ul>
Altitude during operation relating to sea level	
<ul style="list-style-type: none"> <li>Installation altitude above sea level, max.</li> </ul>	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual
<b>connection method</b>	
ET-Connection	
<ul style="list-style-type: none"> <li>via BU/BA Send</li> </ul>	No
<b>Dimensions</b>	
Width	35 mm
Height	147 mm
Depth	129 mm
<b>last modified:</b>	3/31/2023 