zQSFP+/QSFP28

TE Internal #: 2170790-3

QSFP28/56, Cage Assembly, Signal, Operating Temperature Range -40-85 °C [-40-185 °F], 4 Ports, Port Matrix Configuration 1 x 4,

Included Lightpipe

View on TE.com >



Connectors > Pluggable IO Connectors & Cages





Pluggable I/O Product Type: Cage Assembly

Sealable: No

Circuit Application: Signal

Operating Temperature Range: -40 - 85 °C [-40 - 185 °F]

Number of Ports: 4

Features

Product Type Features

Heat Sink
Ganged
Cage Assembly
No
QSFP28/56

Configuration Features

Number of Rear EONs per Port Column	1
Number of Ports	4
Port Matrix Configuration	1 x 4

Body Features

Heat Sink Finish	Anodized Black
Heat Sink Height	6.5 mm[.256 in]
Heat Sink Height Class	Custom
Heat Sink Style	Pin

Contact Features

PCB Contact Termination Area Plating Material Tin	
---	--

Termination Features



Termination Post & Tail Length	2.05 mm[.081 in]
Termination Method to PCB	Through Hole - Press-Fit
Housing Features	
Cage Material	Nickel Silver
Dimensions	
PCB Thickness (Recommended)	1.57 mm[.062 in]
Usage Conditions	
Operating Temperature Range	-40 - 85 °C[-40 - 185 °F]
Operation/Application	
Pluggable I/O Applications	Thermally Enhanced
Circuit Application	Signal
Industry Standards	
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Method	Box & Tray
Other	
Included Lightpipe	Yes
EMI Containment Feature Type	Internal/External EMI Springs

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # CAT-C11-Z806726

QSFP28 to QSFP28 Cable Assembly:
30 AWG



TE Part # CAT-C11-N49 QSFP28-Two QSFP28 Cable Assembly: 30 AWG



TE Part # CAT-C11-Z8

QSFP28 to QSFP28 Cable Assembly:
26 AWG



TE Part # CAT-C11-N490333

QSFP28-Four SFP+ Cable Assembly:
30 AWG



TE Part # CAT-C11-N490325

QSFP28-Four SFP+ Cable Assembly:
26 AWG



TE Part # CAT-Q17-N490325 QSFP56 to QSFP56 Cable Assembly: 30 AWG



TE Part # CAT-Q17-N49033 QSFP56-Two QSFP56 Cable Assembly: 30 AWG



TE Part # CAT-Q17-N49011 QSFP56-Four SFP56 Cable Assembly: 30 AWG



TE Part # CAT-Q17-N490333 QSFP56-Four SFP56 Cable Assembly: 26 AWG



TE Part # 1888810-2 EMI/Dust Cover,XFP And QSFP



TE Part # 1551920-2 zQSFP+ connector assembly



TE Part # CAT-C11-Q17 QSFP56 to QSFP56 Cable Assembly: 26 AWG



09/25/2024 12:17PM | Page 3



Also in the Series zQSFP+/QSFP28







Pluggable I/O Cable Assemblies(78)



Pluggable IO Connectors & Cages(424)

Customers Also Bought



TE Part #2170088-1
ZSFP+ Connector,30u"



TE Part #1551920-2 zQSFP+ connector assembly



TE Part #2110819-1 QSFP+ Enh EVERCLEAR PT Conn



TE Part #2304921-1
ZSFP+ 1X8 CAGE ASSEMBLY, PRESS-FIT



TE Part #2007562-5 SFP+assy 2x6 Spring Fingers 4 LP Sn



TE Part #2053453-7 QSFP-Four SFP+ I/O Cable Assembly 30 AWG



TE Part #2299940-1
ZQSFP+ STACKED REC ASSEMBLY
2X1,4LP HS

TE Part #2321493-4
BUS BAR ASSEMBLY, CROWN CLIP
SOCKET

TE Part #2360512-4
CA, 2 POS BUSBAR MATING TO R
LUG 180MM

Documents

Product Drawings

CAGE ASSY, 1X4, QSFP28, SPRING, HS, LP

English

CAD Files

3D PDF

3D



Customer View Model

ENG_CVM_CVM_2170790-3_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2170790-3_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2170790-3_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

QSFP28/56 and zQSFP+ Interconnects

English

Product Specifications

Application Specification

English