



7	压柄	SUS	
6	触点	银合金	
5	端子	C2680	镀银
4	弹片	C5210	
3	按钮	PBT	白色
2	上盖	PBT	黑色
1	底座	PBT	白色
	序号	名称	材料
			备注

<b>Rating</b>	DC30V 100mA	<b>Electrical Life</b>	1000,000 cycles
<b>Contact Resistance</b>	500mΩ Max	<b>Mechanical Life</b>	1000,000 cycles
<b>Insulation Resistance</b>	>100MΩ DC500V	<b>Ambient Temp. Used</b>	-25℃ to +85℃
<b>Withstand Voltage</b>	AC500V 1min.	<b>Ambient Humidity Used</b>	≤85% at +40℃
<b>Soldering Temper.</b>	235±5℃ 5s	<b>Operating Force</b>	20±15gf max

ΔX	ANGULAR	±5°	DSND	DATE	SCALE: N/A	MODEL TYPE: MICRO SWITCH
ΔX	L ≤ 4	±0.2	DWN	DATE	VIEW: ①	PART NO.:
ΔX	4 < L ≤ 16	±0.3	CHKD	DATE	UNIT: mm	DWG NO.: DM1-135P
ΔX	16 < L ≤ 63	±0.4	APPD	DATE	SIZE: A4	WEIGHT 1.0g
MARK	L > 63	±0.5				SHEET 1/1
	UNSPECIFIED TOLERANCES					REVISION A0
XKB INDUSTRIAL PRECISION CO., LIMITED						

www.xk-dg.cn www.hellokko.com www.hellokko.cn