

**PRODUCTS**

- Rocker switches
- Pushbutton switches
- Toggle switches
- Slide switches
- Rotary switches
- Foot switches
- Tact and key switches
- Snap-action switches**
- Micro-signal switches
- ECO switches
- Sensors
- Systems and modules
- Accessories
- General information
- Catalog request / download

 PRODUCTS ▶ [SNAP-ACTION SWITCHES](#)

## Snap-action switches

### SERIES 1045 - SUBMINIATUR SNAP-ACTION SWITCH IP 67 - TO 10(3) A 250 V AC 1E4

[◀ Show previous product](#)
[Show next product ▶](#)

1045.1151

[Drawing](#)
[Accessories](#)


Similar to original product

[→ Print data sheet](#)

Product number	1045.1151
Switching function	Changeover switch (SPDT momentary)
Number of poles	1-pole
connections	Quick-connect terminal, 2.8 x 0.5, sealed
Mechanical life endurance	10E6
Rating IEC / Rating North America	1 A 250 V AC 100E3
Design	DIN 41635 B
Contact resistance (new condition)	< 100 (1 A 12 V DC) mOhm
Insulation resistance (new condition)	> 100 (500 V DC) MOhm
Proof tracking	250 PTI
Protection type	Connection IP 00 Actuator IP 67
Ambient temperature	-40 °C ... +100 °C
Flammability	UL 94 V-0
Glow wire test temperature	850 °C
Actuators and additional actuators	standard actuator
Contact material	Au
Operating force	≤ 1.9 N
Bounce time	< 5 ms
Difference travel max.	0.2 mm
Free position (FP) max.	9.15 ±0.15 mm
Operating position (OP)	8.4 ±0.3 mm
Permissible total travel position	7.6 mm
Approval marks	cULus (61058) / ENEC 15
Suitable for appliances of protection class	I
Shop / Stock version	