

## R-RBP Rawlbolt - Bolt Projecting for use in cracked and non-cracked concrete.

World's most popular all-purpose expanding shield anchor - bolt projecting version



### Approvals and Reports

- ETA-11/0479 (M6 - M20)



### Product information

#### Features and benefits

- RAWLBOLT® - first ever mechanical anchor in the world, forerunner of all of the later mechanical anchors
- For use in cracked and non-cracked concrete (ETA option 1), hollow-core slabs, flooring blocks and ceramics
- Product recommended for applications requiring fire resistance
- Three-pieces expanding sleeve of maximum expansion provides optimal load and safety of use in any substrate
- Wide range of diameters (M6 to M24)

#### Applications

- Roller shutter doors
- Fire doors
- Steelwork
- Security grills
- Heavy machinery
- Pipework/duct work support

#### Base materials

##### Approved for use in:

- Cracked concrete C20/25-C50/60
- Non-cracked concrete C20/25-C50/60
- Unreinforced concrete
- Reinforced concrete

##### Also suitable for use in:


- Solid clay brick 20MPa
- Hollow Sand-lime Brick 15MPa
- Natural Stone
- Hollow Lightweight Concrete Block
- Hollow-core Slab
- Concrete hollow floor block (eg. Teriva)

### Installation guide




1. Drill a hole of required diameter and depth. Note: When fixing into brickwork, mortar joints should be avoided
2. Clear the hole of drilling dust and debris (using blowpump or equivalent method)
3. Remove nut and washer and insert anchor into hole. Tap home with hammer until flush with surface
4. Position fixture over the projecting bolt
5. Add washer and nut and tighten to recommended torque

**Product information**



Size	Product Code	Anchor			Fixture		
		Diameter	External diameter	Length	Max. thickness	Min. thickness	Hole diameter
		$d$	$d_{nom}$	$L$	$t_{fix}$		$d_f$
		[mm]	[mm]	[mm]	[mm]	[mm]	[mm]
M6	R-RBP-M06/10W	6	12	65	10	-	6,5
	R-RBP-M06/25W	6	12	80	25	-	6,5
	R-RBP-M06/60W	6	12	115	60	-	6,5
M8	R-RBP-M08/10W	8	14	75	10	-	9
	R-RBP-M08/25W	8	14	90	25	-	9
	R-RBP-M08/60W	8	14	125	60	-	9
M10	R-RBP-M10/15W	10	16	90	15	-	11
	R-RBP-M10/30W	10	16	105	30	-	11
	R-RBP-M10/60W	10	16	135	60	-	11
M12	R-RBP-M12/15W	12	20	110	15	-	13
	R-RBP-M12/30W	12	20	125	30	-	13
	R-RBP-M12/75W	12	20	170	75	-	13
M16	R-RBP-M16/15W	16	25	150	15	-	17
	R-RBP-M16/35W	16	25	170	35	10	17
	R-RBP-M16/75W	16	25	210	75	35	17
M20	R-RBP-M20/15W	20	32	170	15	-	22
	R-RBP-M20/30W	20	32	185	30	10	22
	R-RBP-M20/100W	20	32	255	100	30	22
M24	R-RBP-M24/75W	24	38	255	75	-	26
	R-RBP-M24/150W	24	38	300	150	75	26

### Installation data



Size		M6	M8	M10	M12	M16	M20	M24
Thread diameter	d [mm]	6	8	10	12	16	20	24
Hole diameter in substrate	d <sub>0</sub> [mm]	12	14	16	20	25	32	38
Installation torque	T <sub>inst</sub> [Nm]	6.5	15	27	50	120	230	400
Wrench size	Sw [mm]	10	13	17	19	24	30	24
Min. hole depth in substrate	h <sub>0</sub> [mm]	50	55	65	85	125	140	160
Installation depth	h <sub>nom</sub> [mm]	45	50	60	80	120	135	155
Min. substrate thickness	h <sub>min</sub> [mm]	100	100	100	100	142.5	172.5	240
Min. spacing	s <sub>min</sub> [mm]	35	40	50	60	95	115	210
Min. edge distance	c <sub>min</sub> [mm]	53	60	75	90	143	173	188

### Mechanical properties

Size		M6	M8	M10	M12	M16	M20	M24
Nominal ultimate tensile strength - tension	f <sub>uk</sub> [N/mm <sup>2</sup> ]	500	500	500	500	500	500	500
Nominal yield strength - tension	f <sub>yk</sub> [N/mm <sup>2</sup> ]	400	400	400	400	400	400	400
Cross sectional area - tension	A <sub>s</sub> [mm <sup>2</sup> ]	20.1	36.6	58	84.3	157	245	353
Elastic section modulus	W <sub>el</sub> [mm <sup>3</sup> ]	12.7	31.2	62.3	109.2	277.5	540.9	935.5
Characteristic bending resistance	M <sup>0</sup> <sub>Rk,s</sub> [Nm]	7.6	19	37	66	166	325	561
Design bending resistance	M [Nm]	6.1	15	30	52	133	260	449

### Basic performance data

Performance data for single anchor without influence of edge distance and spacing

Size		M6	M8	M10	M12	M16	M20	M24
<b>MEAN ULTIMATE LOAD</b>								
<b>TENSION LOAD N<sub>Ru,m</sub></b>								
NON-CRACKED CONCRETE	[kN]	6.36	8.35	15.24	18.48	48.77	56.55	94.30
CRACKED CONCRETE	[kN]	4.06	5.31	7.12	12.01	18.24	34.16	-
<b>SHEAR LOAD V<sub>Ru,m</sub></b>								
NON-CRACKED CONCRETE	[kN]	6.04	10.98	17.40	25.30	47.10	73.50	105.90
CRACKED CONCRETE	[kN]	6.04	10.98	17.40	25.30	47.10	73.50	-
<b>CHARACTERISTIC LOAD</b>								
<b>TENSION LOAD N<sub>Rk</sub></b>								
NON-CRACKED CONCRETE	[kN]	6.00	7.50	12.00	16.00	40.00	50.00	70.00
CRACKED CONCRETE	[kN]	4.00	5.00	6.00	12.00	16.00	30.00	-
<b>SHEAR LOAD V<sub>Rk</sub></b>								
NON-CRACKED CONCRETE	[kN]	5.03	7.50	12.00	21.08	39.25	61.25	88.30
CRACKED CONCRETE	[kN]	4.00	5.00	6.00	21.08	39.25	61.25	-

### Basic performance data

Size		M6	M8	M10	M12	M16	M20	M24
<b>DESIGN LOAD</b>								
<b>TENSION LOAD <math>N_{Rd}</math></b>								
NON-CRACKED CONCRETE	[kN]	3.33	4.17	6.67	8.89	22.22	27.78	38.90
CRACKED CONCRETE	[kN]	2.22	2.78	3.33	6.67	8.89	16.67	-
<b>SHEAR LOAD <math>V_{Rd}</math></b>								
NON-CRACKED CONCRETE	[kN]	3.33	4.17	6.67	16.86	31.40	49.00	70.60
CRACKED CONCRETE	[kN]	2.22	2.78	3.33	16.86	31.40	49.00	-
<b>RECOMMENDED LOAD</b>								
<b>TENSION LOAD <math>N_{rec}</math></b>								
NON-CRACKED CONCRETE	[kN]	2.38	2.98	4.76	6.35	15.87	19.84	27.80
CRACKED CONCRETE	[kN]	1.59	1.99	2.38	4.76	6.35	11.91	-
<b>SHEAR LOAD <math>V_{rec}</math></b>								
NON-CRACKED CONCRETE	[kN]	2.38	2.98	4.76	12.05	22.43	35.00	50.40
CRACKED CONCRETE	[kN]	1.59	1.99	2.38	12.05	22.43	35.00	-

### Design performance data

Size		M6	M8	M10	M12	M16	M20	M24
Effective embedment depth	$h_{ef}$ [mm]	35.00	40.00	50.00	60.00	95.00	115.00	125.00
<b>TENSION LOAD</b>								
<b>STEEL FAILURE</b>								
Characteristic resistance	$N_{Rk,s}$ [kN]	10.05	18.30	29.00	42.15	78.50	122.50	176.50
Design resistance $V_{M6} = 1.5$	$N_{Rd,s}$ [kN]	6.70	12.20	19.33	28.10	52.33	81.67	117.60
<b>PULL-OUT FAILURE; NON-CRACKED CONCRETE C20/25</b>								
Characteristic resistance	$N_{Rk,p}$ [kN]	6.00	7.50	12.00	16.00	40.00	50.00	70.00
Design resistance $V_{M6} = 1.8$	$N_{Rd,p}$ [kN]	3.33	4.17	6.67	8.89	22.22	27.78	38.90
<b>PULL-OUT FAILURE; CRACKED CONCRETE C20/25</b>								
Characteristic resistance	$N_{Rk,p}$	-	4.00	5.00	6.00	12.00	16.00	30.00
Design resistance $V_{M6} = 1.8$	$N_{Rd,p}$	-	2.22	2.78	3.33	6.67	8.89	16.67
Spacing	$s_{cr,N}$ [mm]	105.00	120.00	150.00	180.00	285.00	345.00	375.00
Edge distance	$c_{cr,N}$ [mm]	53.00	60.00	75.00	90.00	143.00	173.00	188.00
<b>SHEAR LOAD</b>								
<b>CONCRETE EDGE FAILURE; NON-CRACKED CONCRETE C20/25</b>								
Edge distance	$c_1$ [mm]	53.00	60.00	75.00	90.00	143.00	173.00	190.00
Characteristic resistance for $c_1$	$V_{Rk,c}$ [kN]	7.38	9.11	13.03	17.72	36.78	50.82	58.89
Design resistance $V_{M6} = 1.8$	$V_{Rd,c}$ [kN]	4.10	5.06	7.24	9.84	20.44	28.23	32.72
<b>CONCRETE EDGE FAILURE; CRACKED CONCRETE C20/25</b>								
Edge distance	$c_1$	-	53.00	60.00	75.00	90.00	143.00	173.00
Characteristic resistance for $c_1$	$V_{Rk,c}$	-	5.16	6.46	9.23	12.55	25.94	35.86
Design resistance $V_{M6} = 1.8$	$V_{Rd,c}$	-	2.87	3.59	5.13	6.97	14.41	19.92
<b>CONCRETE PRY-OUT FAILURE; NON-CRACKED CONCRETE C20/25</b>								
Factor	$k$	-	1.00	1.00	1.00	2.00	2.00	2.00
Characteristic resistance	$V_{Rk,cp}$ [kN]	6.00	7.50	12.00	32.00	80.00	100.00	140.00
Design resistance $V_{M6} = 1.8$	$V_{Rd,cp}$ [kN]	3.33	4.17	6.67	17.78	44.44	55.56	77.78
<b>CONCRETE PRY-OUT FAILURE; CRACKED CONCRETE C20/25</b>								
Factor	$k$	-	1.00	1.00	1.00	2.00	2.00	2.00
Characteristic resistance	$V_{Rk,cp}$	-	4.00	5.00	6.00	24.00	32.00	60.00
Design resistance $V_{M6} = 1.8$	$V_{Rd,cp}$	-	2.22	2.78	3.33	13.33	17.78	33.33
<b>STEEL FAILURE</b>								
Characteristic resistance without lever arm	$V_{Rk,s}$ [kN]	5.03	9.15	14.50	21.08	39.25	61.25	88.30
Design resistance $V_{M6} = 1.25$	$V_{Rd,s}$ [kN]	4.02	7.32	11.60	16.86	31.40	49.00	70.60

## Design performance data

Resistance to tension and shear loads under fire exposure

Size			M6	M8	M10	M12	M16	M20
<b>R (for EI) = 30 min</b>								
<b>TENSION LOAD</b>								
<b>STEEL FAILURE</b>								
Characteristic resistance	$N_{Rk,s}$	[kN]	0.20	0.40	0.90	1.70	3.10	4.90
<b>PULL-OUT FAILURE</b>								
Characteristic resistance	$N_{Rk,p}$	[kN]	1.00	1.30	1.50	3.00	4.00	7.50
<b>CONCRETE CONE FAILURE</b>								
Characteristic resistance	$N_{Rk,c}$	[kN]	1.30	1.80	3.20	5.00	15.70	25.40
<b>SHEAR LOAD</b>								
<b>STEEL FAILURE</b>								
Characteristic resistance without lever arm	$V_{Rk,s}$	[kN]	0.20	0.40	0.90	1.70	3.10	4.90
Characteristic resistance with lever arm	$M_{Rk,s}$	[kN]	0.20	0.40	1.10	2.60	6.70	13.00
<b>R (for EI) = 60 min</b>								
<b>TENSION LOAD</b>								
<b>STEEL FAILURE</b>								
Characteristic resistance	$N_{Rk,s}$	[kN]	0.20	0.30	0.80	1.30	2.40	3.70
<b>PULL-OUT FAILURE</b>								
Characteristic resistance	$N_{Rk,p}$	[kN]	1.00	1.30	1.50	3.00	4.00	7.50
<b>CONCRETE CONE FAILURE</b>								
Characteristic resistance	$N_{Rk,c}$	[kN]	1.30	1.80	3.20	5.00	15.70	25.40
<b>SHEAR LOAD</b>								
<b>STEEL FAILURE</b>								
Characteristic resistance without lever arm	$V_{Rk,s}$	[kN]	0.20	0.30	0.80	1.30	2.40	3.70
Characteristic resistance with lever arm	$M_{Rk,s}$	[kN]	0.10	0.30	1.00	2.00	5.00	9.70
<b>R (for EI) = 90 min</b>								
<b>TENSION LOAD</b>								
<b>STEEL FAILURE</b>								
Characteristic resistance	$N_{Rk,s}$	[kN]	0.10	0.30	0.60	1.10	2.00	3.20
<b>PULL-OUT FAILURE</b>								
Characteristic resistance	$N_{Rk,p}$	[kN]	1.00	1.30	1.50	3.00	4.00	7.50
<b>CONCRETE CONE FAILURE</b>								
Characteristic resistance	$N_{Rk,c}$	[kN]	1.30	1.80	3.20	5.00	15.70	25.40
<b>SHEAR LOAD</b>								
<b>STEEL FAILURE</b>								
Characteristic resistance without lever arm	$V_{Rk,s}$	[kN]	0.10	0.30	0.60	1.10	2.00	3.20
Characteristic resistance with lever arm	$M_{Rk,s}$	[kN]	0.10	0.30	0.70	1.70	4.30	8.40
<b>R (for EI) = 120 min</b>								
<b>TENSION LOAD</b>								
<b>STEEL FAILURE</b>								
Characteristic resistance	$N_{Rk,s}$	[kN]	0.10	0.20	0.50	0.80	1.60	2.50
<b>PULL-OUT FAILURE</b>								
Characteristic resistance	$N_{Rk,p}$	[kN]	1.00	1.30	1.50	3.00	4.00	7.50
<b>CONCRETE CONE FAILURE</b>								
Characteristic resistance	$N_{Rk,c}$	[kN]	1.00	1.40	2.50	4.00	12.60	20.30
<b>SHEAR LOAD</b>								
<b>STEEL FAILURE</b>								
Characteristic resistance without lever arm	$V_{Rk,s}$	[kN]	0.10	0.20	0.50	0.80	1.60	2.50
Characteristic resistance with lever arm	$M_{Rk,s}$	[kN]	0.10	0.20	0.60	1.30	3.30	6.50

**Product commercial data**

Size	Product Code	Anchor		Quantity [pcs]			Weight [kg]			Bar Codes
		Diameter [mm]	Length [mm]	Box	Outer	Pallet	Box	Outer	Pallet	
M6	R-RBP-M06/10W <sup>1)</sup>	6	65	50	400	16000	1.59	12.7	538.8	5906675283593
	R-RBP-M06/25W <sup>1)</sup>	6	80	50	400	16000	1.73	13.8	582.0	5906675283616
	R-RBP-M06/60W <sup>1)</sup>	6	115	50	50	8000	2.0	2.0	354.0	5906675283630
M8	R-RBP-M08/10W <sup>1)</sup>	8	75	50	400	16000	2.9	22.9	946.8	5906675283654
	R-RBP-M08/25W <sup>1)</sup>	8	90	50	50	8000	3.1	3.1	528.4	5906675283678
	R-RBP-M08/60W <sup>1)</sup>	8	125	50	50	8000	3.7	3.7	614.8	5906675283692
M10	R-RBP-M10/15W <sup>1)</sup>	10	90	50	50	8000	5.0	5.0	825.2	5906675283715
	R-RBP-M10/30W <sup>1)</sup>	10	105	50	50	6000	5.3	5.3	666.0	5906675283739
	R-RBP-M10/60W <sup>1)</sup>	10	135	50	50	8000	6.1	6.1	998.0	5906675283753
M12	R-RBP-M12/15W <sup>1)</sup>	12	110	25	25	4000	4.6	4.6	767.2	5906675283760
	R-RBP-M12/30W <sup>1)</sup>	12	125	25	25	4000	4.9	4.9	818.4	5906675283777
	R-RBP-M12/75W <sup>1)</sup>	12	170	25	25	3000	5.8	5.8	721.8	5906675283784
M16	R-RBP-M16/15W <sup>1)</sup>	16	150	10	10	1600	4.4	4.4	733.5	5906675283791
	R-RBP-M16/35W <sup>1)</sup>	16	170	10	10	1600	4.7	4.7	773.5	5906675283807
	R-RBP-M16/75W <sup>1)</sup>	16	210	10	10	1200	5.3	5.3	662.9	5906675283814
M20	R-RBP-M20/15W <sup>1)</sup>	20	170	10	10	1200	8.0	8.0	985.1	5906675283821
	R-RBP-M20/30W <sup>1)</sup>	20	185	10	10	1200	8.3	8.3	1030.4	5906675283838
	R-RBP-M20/100W <sup>1)</sup>	20	255	10	10	1200	9.9	9.9	1219.2	5906675284781
M24	R-RBP-M24/75W	24	255	5	5	600	7.1	7.1	887.2	5906675283852
	R-RBP-M24/150W	24	300	2	2	400	3.2	3.2	672.0	5906675283845

1) ETA-11/0479 (M6 - M20)