# molex

Part Number: 2153610064

Product Description: 5G mmWave RF Flex-to-Board Plug, 0.35mm Pitch, 0.60mm Mated

Height, Series 5G15 Series Number: 215361

Status: Active

**Product Category:** Board-to-Board

Connectors



#### **Documents & Resources**

## **Drawings**

2153610064\_sd.pdf

3D Models and Design Files

2153610064\_stp.zip

#### **Specifications**

2153600000-AS-000.pdf 2153619200-SPK-200.pdf 2153600000-PS-000.pdf

# **Product Environment Compliance**

## Compliance

GADSL/IMDS	Not Relevant
China RoHS	<b>©</b>
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

## Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

## Multiple Part Industry Compliance Documents

- IPC 1752A Class C

- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

# EU RoHS Certificate of Compliance

# **Part Details**

## General

Status	Active
Category	Board-to-Board Connectors
Series	215361
Description	5G mmWave RF Flex-to-Board Plug, 0.35mm Pitch, 0.60mm Mated Height, Series 5G15
Series Name	0.35, 5G15
Application	Board-to-Board
Component Type	PCB Header
Product Name	5G mmWave,SlimStack
UPC	195842000124

## **Electrical**

Current - Maximum per Contact	0.3A, 1.0A
Voltage - Maximum	50V AC (RMS)/DC

# Physical

Breakaway	No
Circuits (Loaded)	6
Circuits (maximum)	6
Color - Resin	Black
Durability (mating cycles max)	10
Glow-Wire Capable	No
Mated Height	0.60mm
Mated Width	2.30mm
Material - Metal	Copper Alloy
Material - Plating Mating	Gold
Material - Plating Termination	Gold

Material - Resin	Liquid Crystal Polymer
Marei Iai - Vezii i	Liquiu Crystai Folymel
Net Weight	2.843/mg
Number of Rows	2
Orientation	Vertical
Packaging Type	Embossed Tape on Reel
PCB Locator	No
PCB Retention	Yes
Pitch - Mating Interface	0.35mm
Pitch - Termination Interface	0.35mm
Plating min - Mating	0.100µm
Plating min - Termination	0.050µm
Polarized to Mating Part	No
Polarized to PCB	No
Temperature Range - Operating	-40° to +85°C
Termination Interface Style	Surface Mount

# Mates With / Use With

# Mates with Part(s)

Description	Part Number
5G mmWave RF Flex-to-Board Receptacle, 0.35mm Pitch, 0.60mm Mated Height, Series 5G15	2153600064

This document was generated on Oct 29, 2024