



TECHNICAL CHARACTERISTICS

MATERIAL
 INSULATOR: PBT
 FLAMABILITY RATING: UL94-V0
 MAX. TEMPERATURE: 220°C 10s
 COLOR: BLACK
 SHIELDING: STEEL TIN PLATED

ENVIRONMENTAL
 OPERATING TEMP.: -40°C UP TO 85°C
 COMPLIANCE: LEAD FREE AND ROHS

CURRENT RATING: 3A MAX
WORKING VOLTAGE: 125V AC
INSULATOR RESISTANCE: >5000 MOHM
DIELECTRIC WITHSTANDING VOLTAGE: 1000V AC/MN

PACKAGING
 TRAY

DIMENSION

NB PIN	A	B	C	D	E
9	16.92	25.00	30.80	15.80	19.20
15	25.25	33.30	39.20	24.00	27.70
25	38.96	47.10	53.10	38.00	41.10
37	55.42	63.50	69.40	54.30	57.30

MALE CRIMP CONTACT
 AWG 20-22 PART NO: 61800413722
 AWG 24-26 PART NO: 61800513722

NOTE : NOT COMPATIBLE WITH HOOD 6180xx25311

RoHS Compliant			
I	10-APR-13	MEASURE	AR
H	05-MAR-13	NOTE	QL
REV	DATE	FILE	BY

PROJECTION:

APPROVAL: RJ

GENERAL TOLERANCE
 .X = +/- 0.2
 .XX = +/- 0.15

UNIT: MM
 SCALE:
 SHEET: 1/1
 DRAW: PEARL



DESCRIPTION: D SUB MALE TERMINAL HOUSING

WERI PART NO: 618 0xx 217 122

SIZE
A4