2909692

https://www.phoenixcontact.com/us/products/2909692

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Migration cable for Bailey INFI 90 to modern control platforms. Open-end cable for universal configurations, twisted pair, 5.0 m

Your advantages

- Individual wire marking: 1, 2, 3, 4, etc.
- Twisted-pair wires fitted with ferrules
- · Open end at one end
- · MR connector at one end

Commercial data

Item number	2909692
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	C429
Product key	CK2BL4
GTIN	4055626682334
Weight per piece (including packing)	882 g
Weight per piece (excluding packing)	840 g
Customs tariff number	85444290
Country of origin	US

PHŒNIX

2909692

https://www.phoenixcontact.com/us/products/2909692



Technical data

Product type	System cable
ronmental and real-life conditions	
nbient conditions	
Ambient temperature (operation)	-20 °C 50 °C
Ambient temperature (storage/transport)	-20 °C 70 °C
trical properties	
Operating voltage (AC)	≤ 125 V AC
Operating voltage (DC)	≤ 125 V DC
Current (Per path)	≤ 1 A
le/line	
	5 m
Cable length	5 m
Number of positions Shielded	19
	Assembled shielded round cable
Conductor type	Assembled shielded round cable
Conductor structure signal line AWG signal line	24
Conductor cross section	24 19x 0.21 mm ²
Halogen-free	no
MR36F (1)	() = black
MR36F (2)	() = black () = red
MR36F (3)	() = black
MR36F (4)	() = white
MR36F (5)	() = black
MR36F (6)	() = green
MR36F (7)	() = black
MR36F (8)	() = blue
MR36F (9)	() = black
MR36F (10)	() = yellow
MR36F (11)	() = black
MR36F (12)	() = brown
MR36F (13)	() = black
MR36F (14)	() = orange
MR36F (15)	() = red
MR36F (16)	() = white
MR36F (17)	() = red
MR36F (18)	() = green
MR36F (19)	() = red



2909692

https://www.phoenixcontact.com/us/products/2909692

MR36F (20)	() = blue
MR36F (21)	() = red
MR36F (22)	() = yellow
MR36F (23)	() = red
MR36F (24)	() = brown
MR36F (25)	() = red
MR36F (26)	() = orange
MR36F (27)	() = green
MR36F (28)	() = white
MR36F (29)	() = green
MR36F (30)	() = blue
MR36F (31)	() = green
MR36F (32)	() = yellow
MR36F (33)	() = green
MR36F (34)	() = brown
MR36F (35)	() = green
MR36F (36)	() = orange

Connection data

Field level


Connection method	D-SUB pin strip
Number of connections	1
Number of positions	37

Controller level

Connection method	Twisted pair
Number of positions	37
Note	The wires are marked and fitted with ferrules. The braided shield is routed to a separate cable end.

Notes

Notes on operation	For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-
	party products, the specifications, and the safety and warning
	instructions of the respective third-party manufacturer must also
	be met.



2909692

https://www.phoenixcontact.com/us/products/2909692




Classifications

ECLASS

ECLASS-11.0	27242220
ECLASS-12.0	27242220
ECLASS-13.0	27242220

ETIM

	ETIM 8.0	EC000237
UNSPSC		
	UNSPSC 21.0	26121600



2909692

https://www.phoenixcontact.com/us/products/2909692

PHŒNIX CONTACT

Environmental product compliance

EU REACH SVHC

REACH candidate substance (CAS No.)

No substance above 0.1 wt%

2909692

https://www.phoenixcontact.com/us/products/2909692



Accessories

KME - Cable marker carrier

0807083 https://www.phoenixcontact.com/us/products/0807083



Cable marker carrier, white, unlabeled, mounting type: Assembly with cable ties, cable diameter: > 5 mm, lettering field size: 20 x 8 mm

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com