TE Internal #: 2273109-5

M8 to M12 Cable Assembly, 4 Position, 2 m, Sensor/Actuator, Code

A, M8 Plug, M12 Socket, Double Ended, Plastic

View on TE.com >



Cable Assemblies > Copper Cable Assemblies > M8/M12 Cable Assemblies > M8 MS - M12 FS CABLE ASSY BL



M8/M12 Application Type: Sensor/Actuator

Number of Positions: 4

Connector & Keying Code: A

Cable Assembly Type: M8 to M12

Cable Assembly (End A): M8 Plug

All M8 MS - M12 FS CABLE ASSY BL (19)

Features

Product Type Features

Cable Assembly Type	M8 to M12
Cable Assembly (End A)	M8 Plug
Cable Assembly (End B)	M12 Socket
Configuration Features	
Number of Positions	4
Electrical Characteristics	
Operating Voltage	34 VAC
Body Features	
Cable Color	Black
	Black
Cable Color	
Cable Color Connector Color (End B)	Black
Cable Color Connector Color (End B) Connector Color (End A)	Black
Cable Color Connector Color (End B) Connector Color (End A) Jacket Material	Black Black PUR

4 A

Contact Current Rating (Max)



Thread Size Connector Orientation (End A) Connector Orientation (End B) Housing Features Housing Material Plastic Dimensions Outside Cable Diameter 4.4 mm[.173 in] Wire Size Jage Conditions Operating Temperature Range Operating Temperature Range Augustion M8/M12 Application Type Sensor/Actuator Shielded No Packaging Features Packaging Method Box Other Field Serviceable Cable Assembly Length Straight Advantable Plastic Pastic Source She over (-40 – 40 – 80 °C[-40 – 176 °F] No Packaging Features Packaging Method Dover (-40 – 80 °C[-40 – 176 °F] Sensor/Actuator No Packaging Features Packaging Method Dover (-40 – 80 °C[-40 – 176 °F] Operation (-40 – 80 °C[-40 – 176		
Connector Orientation (End B) Housing Features Housing Material Plastic Dimensions Outside Cable Diameter Vire Size Usage Conditions Operating Temperature Range Operation/Application M8/M12 Application Type Shielded No Packaging Features Packaging Method Box Other Field Serviceable Yes	Thread Size	M8 x M12
Housing Features Housing Material Plastic Dimensions Outside Cable Diameter 4.4 mm[.173 in] Wire Size	Connector Orientation (End A)	Straight
Housing Material Plastic Dimensions Outside Cable Diameter 4.4 mm[.173 in] Wire Size .326 mm² Usage Conditions Operating Temperature Range -40 - 80 °C[-40 - 176 °F] Operation/Application M8/M12 Application Type Sensor/Actuator Shielded No Packaging Features Packaging Method Box Other Field Serviceable Yes	Connector Orientation (End B)	Straight
Dimensions Outside Cable Diameter 4.4 mm[.173 in] Wire Size .326 mm² Usage Conditions Operating Temperature Range -40 – 80 °C[-40 – 176 °F] Operation/Application M8/M12 Application Type Sensor/Actuator Shielded No Packaging Features Packaging Method Box Other Field Serviceable Yes	Housing Features	
Outside Cable Diameter 4.4 mm[.173 in] Wire Size .326 mm² Usage Conditions Operating Temperature Range -40 - 80 °C[-40 - 176 °F] Operation/Application M8/M12 Application Type Sensor/Actuator Shielded No Packaging Features Packaging Method Box Other Field Serviceable Yes	Housing Material	Plastic
Wire Size Usage Conditions Operating Temperature Range -40 – 80 °C[-40 – 176 °F] Operation/Application M8/M12 Application Type Sensor/Actuator Shielded No Packaging Features Packaging Method Box Other Field Serviceable Yes	Dimensions	
Usage Conditions Operating Temperature Range -40 – 80 °C[-40 – 176 °F] Operation/Application M8/M12 Application Type Sensor/Actuator Shielded No Packaging Features Packaging Method Box Other Field Serviceable Yes	Outside Cable Diameter	4.4 mm[.173 in]
Operating Temperature Range -40 – 80 °C[-40 – 176 °F] Operation/Application M8/M12 Application Type Sensor/Actuator Shielded No Packaging Features Packaging Method Box Other Field Serviceable Yes	Wire Size	.326 mm²
Operation/Application M8/M12 Application Type Sensor/Actuator Shielded No Packaging Features Packaging Method Box Other Field Serviceable Yes	Usage Conditions	
M8/M12 Application Type Shielded No Packaging Features Packaging Method Box Other Field Serviceable Yes	Operating Temperature Range	-40 - 80 °C[-40 - 176 °F]
Shielded No Packaging Features Packaging Method Box Other Field Serviceable Yes	Operation/Application	
Packaging Features Packaging Method Box Other Field Serviceable Yes	M8/M12 Application Type	Sensor/Actuator
Packaging Method Other Field Serviceable Yes	Shielded	No
Other Field Serviceable Yes	Packaging Features	
Field Serviceable Yes	Packaging Method	Box
	Other	
Cable Assembly Length 2 m	Field Serviceable	Yes
	Cable Assembly Length	2 m

Product Compliance

Cable Assembly Configuration

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JAN 2022 (223) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Double Ended



Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Customers Also Bought





Documents

Product Drawings

M8 strgt plug to M12 strgt socket AA

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2273109-5_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2273109-5_A.3d_igs.zip



English

Customer View Model

ENG_CVM_CVM_2273109-5_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

M8 / M12 Connector System Catalog

English

Product Specifications

Product Specification

English