



**TECHNICAL**

AGENCY APPROVAL: cULus  
 RATED SUPPLY VOLTAGE: 240 VAC  
 RATED CURRENT: UP TO 20 AMPS  
 RESET TYPE: AUTO/MANUAL  
 OPERATING FREQUENCY: 60 Hz  
 TYPE: CLASS A  
 GROUND TRIP CURRENT: 5mA +/- 1mA  
 OVERLOAD CURRENT: 120 AMPS, 50% INDUCTIVE  
 INSULATION VOLTAGE: 1,500 VRMS - 1 MINUTE  
 ENDURANCE OPERATIONS: 3000 OPERATIONS  
 ENCLOSURE: TYPE 4X, IP69, IP69K

MATERIAL NO.	PART NO.	"L" DIMENSION	"A" DIMENSION	POWER-UP
1301530157	24052-1MLDA	2 FT 9 IN	1 FT	AUTO
1301530158	24052-1MLDM	2 FT 9 IN	1 FT	MANUAL

FUNCTIONAL SYMBOLS $\frac{F}{A} = 0$ $\frac{E}{C} = 0$ $\frac{E}{P} = 0$	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		DIMENSION UNITS: <b>INCH</b> SCALE: <b>NTS</b>		CURRENT REV DESC: NEW SALES DRAWING CREATED				
	GENERAL TOLERANCES (UNLESS SPECIFIED) ANGULAR TOL ± °		EC NO: 727155 DRWN: VBSUTHKARP 2022/11/03 CHK'D: DNGUYEN62 2022/12/16 APPR: WLEUNG 2022/12/29		INLINE GFCI 20A, 240V W/ MOLDED PLUG/CONNECTOR L6-20				
DIVISIONAL SYMBOLS 4 PLACES ± 3 PLACES ± 2 PLACES ± 1 PLACE ± 0 PLACES ±	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION		DRAWING: <b>C-SIZE</b> SERIES: <b>130153</b>		PRODUCT CUSTOMER DRAWING		
	INITIAL REVISION: DRWN: VBSUTHKARP 2022/11/03 APPR: WLEUNG 2022/12/29		DOCUMENT NUMBER: <b>1301530157</b>		DOC TYPE: PSD DOC PART: 000 REVISION: <b>A</b>		MATERIAL NUMBER: SEE TABLE CUSTOMER: GENERAL MARKET		SHEET NUMBER: 1 OF 1