MICRO SWITCH
FREEPORT ILLINOIS, U.S.A
A DIVISION OF HONEYWELL
FED. MFG. CODE 91929

SWITCH - BASIC

CATALOG LISTING
YA-2RQ81245-D6
ADM9715



NOTES
1. MOUNTING HOLES WILL ACCEPT PINS OR SCEWS OF .139 MAX DIA ON 1.000±.002 CENTERS
2. SWITCH WILL WITHSTAND TEMPERATURES OF 250° F
3. HARWARE FURNISHED UNNASSEMBLED

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

THIRD ANGLE PROJECTION

CHARACTERISTICS

OPERATING FORCE — — — — —14-22 OZ

RELEASE FORCE — — — — 9 OZ MIN

DIFFERENTIAL TRAVEL — — —.0020-.0075

OVERTRAVEL — — — — — — —.219 MIN

ELECTRICAL DATA

CONTACT ARRANGEMENT
S P N O

20A—125, 250 OR 480 VAC; 10A—125 VAC "L"
1HP—125 VAC; 2HP—250 VAC
CODE L23 1/2A-125 VDC; 1/4A-250 VDC

L288

L308 20(3)A 250V ~ T85 5E4
L315

SCALE FULL

DO NOT SCALE PRINT

TOLERANCES
APPLY TO DESIGN UNITS. CONVERSIONS ARE ONLY FOR REFERENCE. UNLESS NOTED, TOLERANCES ARE ±

	DIM. mm	TOL. mm/in	DIM. in	TOL. mm/in
NO PLACES	X	1/.04		
ONE PLACE	X.X	0.4/.016	X.X	0.8/.03
TWO PLACES	X.XX	0.15/.006	X.XX	0.38/.015
THREE PLACES			X.XXX	0.13/.005
ANGLES				

DESIGN UNITS: SI METRIC ☐ US CUSTOMARY ☒

WEIGHT .093 LB

CATALOG LISTING YA-2RQ81245-D6 PAGE 1 OF 1

ISSUE 6 M RJ 17 FEB 06

REPLACES 205876

REVISIONS

A	207383	CSL 10 FEB 03	27 MAY 04
B	207555	CSL 4 MAR 03	AK
C	0000831	CSL 10 JUL 03	
D	0005639	BM 27 MAY 04	CHECK
E	0018388	TGP 17 FEB 06	25 JUN 02

CHECK S A V

RASTER DRAWN 25 JUN 02 G J W

Downloaded from Arrow.com.