

## EUROCARD | Eurocard Type B

TE Internal #: 5536446-5

Receptacle, Board-to-Board, 32 Position, 2.54 mm [.1 in] Centerline, Printed Circuit Board, 2 Row, Vertical, Eurocard Type B, Eurocard

Connectors


View on TE.com >



Connectors > PCB Connectors > Backplane Connectors > Eurocard Connectors











Connector & Housing Type: Receptacle

Connector System: Board-to-Board

Termination Post & Tail Length: 3.3 mm [.13 in]

Number of Positions: 32

Centerline (Pitch): 2.54 mm [.1 in]

## **Features**

## **Product Type Features**

| Connector & Housing Type          | Receptacle            |
|-----------------------------------|-----------------------|
| Connector System                  | Board-to-Board        |
| Connector & Contact Terminates To | Printed Circuit Board |
| DIN Size                          | Half                  |
| DIN Level                         | II                    |

## **Configuration Features**

| Number of Positions        | 32       |
|----------------------------|----------|
| Number of Rows             | 2        |
| PCB Mount Orientation      | Vertical |
| Number of Columns          | 16       |
| Number of Signal Positions | 32       |
| Rows Loaded                | А, В     |

### **Electrical Characteristics**

| Operating Voltage 250 VAC |
|---------------------------|
|---------------------------|



# **Body Features**

| Primary Product Color                                   | Gray                           |
|---|--------------------------------|
| Contact Features  |                                |
| PCB Contact Termination Area Plating Material Thickness | 2.54 – 5.08 μm[100 – 200 μin]  |
| Contact Layout  | Inline                         |
| Contact Type  | Socket                         |
| Contact Underplating Material Thickness                 | 1.27 μm[50 μin]                |
| Contact Mating Area Plating Material Thickness          | .76 μm[30 μin]                 |
| Contact Mating Area Plating Material                    | Gold                           |
| Contact Underplating Material                           | Nickel                         |
| PCB Contact Termination Area Plating Material           | Tin                            |
| Contact Base Material                                   | Copper Alloy                   |
| Termination Features                                    |                                |
| Termination Method to PCB                               | Through Hole - Solder          |
| Termination Post & Tail Length                          | 3.3 mm[.13 in]                 |
| Mechanical Attachment                                   |                                |
| Mating Alignment Type                                   | Polarization                   |
| Mating Retention  | Without                        |
| Mating Alignment  | With                           |
| PCB Mount Alignment                                     | Without                        |
| Panel Mount Feature                                     | Without                        |
| PCB Mount Retention                                     | With                           |
| PCB Mount Retention Type                                | Boardlock                      |
| Connector Mounting Type                                 | Board Mount                    |
| Housing Features  |                                |
| Housing Material  | Polymer - GF                   |
| Centerline (Pitch)                                      | 2.54 mm[.1 in]                 |
| Dimensions  |                                |
| Connector Length  | 53.34 mm[2.1 in]               |
| Connector Height  | 11.5 mm[.453 in]               |
| Connector Width   | 8.05 mm[.317 in]               |
| PCB Thickness (Recommended)                             | 1.57 – 2.36 mm[.062 – .093 in] |



| Row-to-Row Spacing                          | 2.54 mm[.1 in]             |
|---|----------------------------|
| Usage Conditions                            |                            |
| Operating Temperature Range                 | -55 – 105 °C[-67 – 221 °F] |
| Operation/Application                       |                            |
| Circuit Application                         | Signal                     |
| Industry Standards                          |                            |
| Compatible With Approved Standards Products | CSA LR7189, UL E28476      |
| UL Flammability Rating                      | UL 94V-0                   |
| Packaging Features                          |                            |
| Packaging Method                            | Box, Box & Tray            |

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU                  | Compliant   |
|---|---|
| EU ELV Directive 2000/53/EC                   | Compliant   |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold   |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC |
| Halogen Content                               | Not Low Halogen - contains Br or Cl > 900 ppm.  |
| Solder Process Capability                     | Wave solder capable to 265°C  |

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts





TE Part # 5536386-5 ASSY,PIN,EUROCARD,TYPE B/2,LEA



TE Part # 536053-5 032 EURO TYPE B PIN ASSY



TE Part # 5536053-5 ASSY,PIN,EUROCARD,TYPE B/2,LEA





# Also in the Series | Eurocard Type B



Eurocard Connectors(34)



Standard Edge Connectors(2)


# Customers Also Bought

















## **Documents**

## **Product Drawings**

ASSEMBLY, RECEPTACLE, EUROCARD, T

English

#### **CAD Files**

**Customer View Model** 

ENG\_CVM\_CVM\_5536446-5\_O.2d\_dxf.zip

English

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_5536446-5\_O.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_5536446-5\_O.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

## **Product Specifications**

**Application Specification** 

English