




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **1.03 – 2.62 mm²**

Mating Tab Width: **6.35 mm [.25 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

Insertion Force	Low
-----------------	-----

Configuration Features

Connection Capacity	Single
Compatible With Wire & Cable Type	Discrete Wire

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Flag
Contact Base Material	Phosphor Bronze
Terminal Plating Material	Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

--	--



Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Wire Insulation Support	With
Mating Retention Type	Dimple

Dimensions

Terminal Material Thickness	.41 mm[.016 in]
Product Length	18 mm[.71 in]
Compatible Insulation Diameter Range	3.1 – 4.3 mm[.12 – .169 in]
Wire Size	1.03 – 2.62 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Industry Standards

Compatible With Agency/Standards Products	UL
---	----

Packaging Features

Packaging Quantity	2000
Packaging Method	Strip/Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 2150938-2 OCEAN_2.0_Applicator-S-110F160F-SSA	TE Part # 7-2150938-7 OCEAN_2.0_SPARE_PART_KIT-110F160F	TE Part # 965430-1 POS LOCK HSG 6,3 2POS	TE Part # 1855627-1 HDM/FA EMPO.110F.160F LM/G CUT

Also in the Series | Positive Lock 250

Automotive Terminals(1)	Crimp Terminal Housings(190)	Insertion & Extraction Tools(3)	Insulation Boots & Sleeves(4)

Quick Disconnects(185)

Customers Also Bought



TE Part #154719
250 HSG. PL MKI REC. BLACK

TE Part #926171-1
Timer Connector Housing

TE Part #DT06-4S
PLG, 4P, GRY, N

TE Part #344263-1
13 WAY REC HSG. SIL. SEALECONO

TE Part #174047-2
040 MULTILOCK PLUG 20P

TE Part #927773-3
JPT REC 2.8 Contact SRC Sn

TE Part #881590-1
ECONOSEAL TAB .070

TE Part #284080-1
.070 TAB CONT.NEW.GEN. (0,3 TO

TE Part #2177791-1
INSULATION COVER,TE,COVER INLET,BK

Documents

Product Drawings

PL 250 REC TERMINAL-FLAG 17-13 PTPB

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_965972-1_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_965972-1_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_965972-1_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications



Application Specification

German