



Part Number : [194390008](#)

Product Description : Loxon Locking Quick Disconnect Housing, Nylon, UL94V-0, Natural

Series Number : 19439

Status : Active

Product Category : Quick Disconnects

Engineering Number : LOCKQD V-0



---

## Documents & Resources

### Drawings

[194390008\\_sd.pdf](#)

[194390008-000.pdf](#)

### Specifications

---

## Product Environment Compliance

### Compliance

|                    |   |
|--------------------|---|
| GADSL/IMDS         | Not Relevant                                    |
| China RoHS         | Not Reviewed per SJ/T 11365-2006                |
| EU ELV             | Not Relevant                                    |
| Low-Halogen Status | Not Reviewed per IEC 61249-2-21                 |
| REACH SVHC         | Not Contained per D(2024)4144-DC (27 June 2024) |
| EU RoHS            | Compliant per EU 2015/863                       |

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D

- Molex Product Compliance Declaration

- IEC-62474

- chemSHERPA (xml)

EU RoHS Certificate of Compliance

---

## Part Details

### General

|              |   |
|--------------|---|
| Status       | Active  |
| Category     | Quick Disconnects   |
| Series       | 19439   |
| Description  | Loxon Locking Quick Disconnect Housing, Nylon, UL94V-0, Natural |
| Product Name | Loxon   |
| Type         | Quick Disconnect Housing  |
| UPC          | 193264611690  |

### Agency

|    |        |
|----|--------|
| UL | E79133 |
|----|--------|

### Electrical

|                   |         |
|-------------------|---------|
| Voltage - Maximum | 600V AC |
|-------------------|---------|

### Physical

|                     |          |
|---------------------|----------|
| Barrel Type         | N/A      |
| Color - Resin       | Natural  |
| Flammability        | 94V-0    |
| Gender              | Female   |
| Glow-Wire Capable   | Yes      |
| Insulated           | N/A      |
| Insulation          | N/A      |
| Lock to Mating Part | Yes      |
| Material - Resin    | Nylon    |
| Net Weight          | 0.905/g  |
| Orientation         | Straight |
| Packaging Type      | Carton   |

|                               |                |
|-------------------------------|----------------|
| Tab Thickness                 | N/A            |
| Tab Width                     | N/A            |
| Temperature Range - Operating | -40° to +105°C |
| Wire Size (AWG)               | N/A            |

---

**Use with Part(s)**

| Description   | Part Number      |
|---|------------------|
| Loxon Locking Quick Disconnect, Female, for 18-20 Wire, Reel, Tab 6.35 x 0.81mm | <u>194390001</u> |
| Loxon Locking Quick Disconnect, Female, for 18-20 Wire, Bag, Tab 6.35 x 0.81mm  | <u>194390002</u> |
| Loxon Locking Quick Disconnect, Female, for 14-16 Wire, Reel, Tab 6.35 x 0.81mm | <u>194390003</u> |
| Loxon Locking Quick Disconnect, Female, for 14-16 Wire, Bag, Tab 6.35 x 0.81mm  | <u>194390004</u> |
| Loxon Locking Quick Disconnect, Female, for 10-12 Wire, Reel, Tab 6.35 x 0.81mm | <u>194390005</u> |
| Loxon Locking Quick Disconnect, Female, for 10-12 Wire, Bag, Tab 6.35 x 0.81mm  | <u>194390006</u> |

---

---