

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

2013

© COPYRIGHT 2013 BY -

ALL RIGHTS RESERVED.

LOC -

DIST -

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	PRODUCTION RELEASE PER ECO-13-011143	1JUL2013	RLM	DM

DATE CODE: YEAR IS REPRESENTED BY THE LAST NUMERICAL DIGIT, EX: 2 = 2012.  
MONTH IS REPRESENTED BY SEQUENTIAL ALPHA CHARACTERS, EX: A = JANUARY.

3. MATERIAL - HOUSING: PLASTIC (BLACK)  
WEDGE LOCK (INCLUDED): PLASTIC (GREEN)  
SEAL: RUBBER  
BUSSBAR: COPPER ALLOY, NICKEL PLATED

2. MAXIMUM CURRENT RATING FOR 2 PIN BUSSBAR IS 13 AMPS

1. THIS RECEPTACLE MATES WITH DT06-2S-\*\*\*\* PLUG.  
(\*\*\*\* = ALL MODIFICATIONS)

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:  
INCHES [mm]

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	±
1 PLC	±
2 PLC	±0.02
3 PLC	±0.005
4 PLC	±
ANGLES	±0°30'0"

MATERIAL

FINISH

-

DWN 25 JUN 2013

R. MESSENGER

CHK 26 JUN 2013

R. MESSENGER

APVD 1 JUL 2013

D. MEYER

PRODUCT SPEC

-

APPLICATION SPEC

-

WEIGHT

6.06g

CUSTOMER DRAWING

TE Connectivity

NAME  
RECEPTACLE ASSEMBLY  
DT 2 PIN BUSSED

SIZE CAGE CODE DRAWING NO RESTRICTED TO

A3 4AFU8 DT04-2P-P060

SCALE 3:1 SHEET 1 OF 1 REV A

1470-19 (3/11)

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[YDT04-2P-P06000000](#)