



FY^{*1)}XX^{*2)}S7-K121

e.g. FL25S7-K121

*1) Y for series FL or FU
 *2) xx No. of contacts 09, 15, 25 or 37

xx	A (mm)	B (mm)	C (mm)
09	30,8	16,4	25
15	39,1	24,7	33,3
25	53	38,5	47,04
37	69,3	54,9	63,5

Technical data for modification (FU)
 Crimp contacts FK20S (AWG 20-24/1,3µm Au) included in delivery.

3	1	Shell	Steel	tin plated
2	1	Insulator rear part	PEI (-55°C - +130°C)	green
1	1	Insulator front part	PBT	green
No.	St.	Part	Type Description/Material	Surface plating/Colour/Class

Technical data for modification (FL)

② Crimp contacts not supplied with connector. Contacts must be ordered separately.

3	1	Shell	Steel	tin plated
3	1	Insulator rear part	PA66 (-55°C - +115°C)	black
1	1	Insulator front part	PBT	black
No.	St.	Part	Type Description/Material	Surface plating/Colour/Class

Measurement without tolerance acc. to ISO 2768-m		SCALE	TITLE
NAME / DATE	25-05-2002	2:1	D-Sub Crimp Connector
DRAWN	Denzinger		
CHECKED	ischter		
	124492/2006		

2	24-02-2006	21782	DWG. NO.	FYxxS7-K121	REV.	2
1			DATE			
			CH-NO.			
			REPLACEMENT FOR:	FYxxS7-K121 g		PAGES
			ORIGINAL DIN A3-DRAWING AS A FILE			1

