





	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					. .	△					. .
△					. .	△					. .
△					. .	△					. .



NOTE 1 HRS MARK SHALL BE OPTIONAL.
2 LEAD CO-PLANARITY SHALL BE 0.1mm MAX.
3 FOR MODIFICATION, ETC., PREVENTIVE HOLE FOR SINK MARK
MAY BE ADDED ACCORDING TO CIRCUMSTANCES.
4 THE DIMENSIONS IN PARENTHESES ARE FOR REFERENCE.

RECOMMENDED LAND PATTERN DIMENSION OF PCB (MOUNTING SIDE)



1	PPS	LIGHT BROWN (UL94V-0)	2	PHOSPHOR BRONZE	CONTACT AREA:GOLD 0.1μ m min.		
					LEAD AREA:TIN-PLATING 1μ m min.		
					UNDER PLATING:NICKEL 2μ m min.		
NO.	MATERIAL	FINISH, REMARKS	NO.	MATERIAL	FINISH, REMARKS		
CODE NO.(OLD)			DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
			T.YANAGISAWA '06.04.24	T.YANAGISAWA '06.04.24	T. Ogawa '06.04.24	H. Okawa '06.04.25	. .
		DRAWING NO.		PART NO.			
SCALE 2 : 1		EDC3-084977-25		FX6-20S-0.8SV(71)			
UNITS 		 HIROSE ELECTRIC CO., LTD		CODE NO.			1/1
				CL576-0101-8-71			

TO