

This document was generated on 05/07/2012 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: Status: Description:	52689-2687 Active 0.50mm Pitch FFC/FPC C Circuits, Lead-Free, High	onnector, SMT, Right Angle, Non-ZIF, Dual Contact Style, 26 Barrier Packaging		
Documents: 3D Model Drawing (PDF) Product Specification I	PS-52689-038 (PDF)	Packaging Specification SPK-52689-003 (PDF) RoHS Certificate of Compliance (PDF)	Series	
Agency Certificat	ion		image - Reference only	
UL		E29179		
General Product Family Series Product Name Physical		FFC/FPC Connectors 52689 N/A	EU RoHS ELV and RoHS Compliant REACH SVHC Contains SVHC: No Low-Halogen Status	
Circuits (Loaded)		26	Not Low-Halogen	
Color - Resin		20 Natural	Need more information on product	
Contact Position		Dual	environmental compliance?	
Durability (mating cycle	es max)	20	Email productcompliance@molex.com	
Entry Angle Flammability		90° Angle	For a multiple part number RoHS Certificate o Compliance, click here	
		94V-0		
Mated Height		2.00mm		
Material - Metal		Phosphor Bronze	Please visit the Contact Us section for any	
Material - Plating Mating		Tin-Bismuth	non-product compliance questions.	
Material - Resin		Nylon		
Number of Rows		1 Diakt Angle		
Orientation PCB Locator		Right Angle		
PCB Locator PCB Retention		No Yes	Search Parts in this Series	
Packaging Type		Embossed Tape on Reel	<u>52689</u> Series	
Pitch - Mating Interface	9	0.50mm		
Polarized to PCB	-	Yes		
Stackable		No		
Temperature Range -	Operating	-20°C to +85°C		
Termination Interface:	Style	Surface Mount		
Wire/Cable Type		FFC/FPC		
Electrical				
Current - Maximum pe	r Contact	0.5A		
Voltage - Maximum		50V		
Material Info				
Poforonco Drow	ing Numbers			
Reference - Draw	-	SPK-52689-003		
Packaging Specification	11	SPK-52689-003 PS-52689-038, RPS-52689-036, RPS-52689-038,		
F TOULOU SPECIFICATION		PS-52689-038, RPS-52689-036, RPS-52689-038, RPS-52689-044		

This document was generated on 05/07/2012

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION