



PS-5850DDX-2PN

PUSH SWITCH

Switch Type
58=5.8×5.8mm

Foot Type
D=Dip

Switch Height
50=5.0mm

Foot Position
2P=2pin

Type
D=Different

Operating Force
A=180gf
B=250gf

Switch Function
L=Lock
N=No Lock

G-Switch Specification:

Operating temperature range: -40℃to+85℃
 Rating: 0.5A.24V DC
 Insulation resistance: 100MΩ min.100V DC
 Dielectric strength: 250V AC for 1 min
 Contact resistance: 100m Ω max.
 Switch lifetime: 30,000Cycles

| | | | | |
|-----|-----------|----------|-----|-----------|
| 8 | | | | |
| 7 | TERMINAL | BRASS | 6 | Ag PLATED |
| 6 | CASE | PPA | 1 | BLACK |
| 5 | LOCK PIN | SUS WIRE | 1 | NATURAL |
| 4 | SPRING | SUS WIRE | 1 | NATURAL |
| 3 | CONTACT | BRONZE | 2 | Ag PLATED |
| 2 | KNOB | PPA | 1 | WHITE |
| 1 | COVER | PPA | 1 | BLACK |
| NO. | PART NAME | MATERIAL | QTY | FINISHING |



b-Switch 品赞科技®

Unless otherwise specified, Tolerance:
 X. ±0.30
 X.x ±0.20
 X.xx ±0.15
 X.xxx ±0.10
 Angles ±3°

G-Switch Electronic (HongKong) CO.,Ltd.

| | | | | | |
|--------------------------|-------------------|------|---------------------|------------------------------|--|
| DESIGN | Feng ² | DATE | 2022.08.12 | Molde code: | |
| CHECKED | | DATE | | PS-5850DDX-2PN | |
| APPROVED | | DATE | | REV.: X1 SCALE: 4:1 UNIT: mm | |
| http://www.dg-switch.com | | | SIZE: A4 SHEET: 1/1 | | |
| TEL:0769-82388879 | | | | | |