



BN 82428

Pozi pan head screws

form Z

Steel case-hardened

zinc plated blue



ISO 4042

Quenched and tempered fasteners ≥ 360 HV and tempered case-hardened fasteners with electroplated coatings: Susceptible to hydrogen embrittlement!

Further notice to residual risks can be found in the introduction section.



[3D Cadenas](#)

Article#	ø nominal	d ₁	d ₂ max.	k max.		m~	t min.	t max.	L
8315299	2,2	2,2	4	1,6	1	2,3	1	1,3	5
3033895									6
3033896									8
3033897									10
3033900									12
3033901									14
3033903									16
3034063	2,5	2,5	5	2,1	1	2,6	1,1	1,5	6
3034065									8
3034066									10
3034069									12
3034072									14
3034077									16
3160639	3	3	5,6	2,4	1	2,9	1,35	1,75	6
3034080									8
3034082									10
3034086									12
3034092									14
3034108									16
3034121									20
3034125									25
3034216	3,5	3,5	7	2,6	2	3,9	1,45	1,9	8
3034217									10
3034218									12
3034220									14
3034221									16

Article#	ø nominal	d ₁	d ₂ max.	k max.		m~	t min.	t max.	L
3034223	3,5	3,5	7	2,6	2	3,9	1,45	1,9	20
3034224									25
3034226	4	4	8	3,1	2	4,4	1,9	2,35	8
3034227									10
3034229									12
3034231									14
3034235									16
3034236									20
3034237									25
3034239	5	5	9,5	3,7	2	4,6	2,3	2,75	10
3034240									12
3034241									14
3034242									16
3034243									20
3034246									25