

**SAK terminal feed-through terminal  
SAK 2.5/35 BL**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-2083  
www.weidmueller.com

The Weidmüller SAK feed-through terminals satisfy the requirements of IEC 60947-1 and are available with rated cross-sections from 0.08 mm<sup>2</sup> to 240 mm<sup>2</sup>.

**General ordering data**

Order No.	<a href="#">0380480000</a>
Part designation	SAK 2.5/35 BL
Version	SAK terminal feed-through terminal, Feed-through terminal, Rated cross-section: 2.5 mm <sup>2</sup> , Screw connection, PA 66, blue
GTIN (EAN)	4008190131869
Qty.	100 pc(s).

**SAK terminal feed-through terminal  
SAK 2.5/35 BL**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-2083  
www.weidmueller.com

**Technical data**

**CSA ratings data**

Certificate no.	12400-129	Voltage size C	600 V
Current size C (CSA)	25 A	Conductor cross-section, max.	10 AWG
Conductor cross-section, min.	26 AWG		

**UL ratings data**

Certificate no.	E60693VOL1SEC14	Voltage size C	600 V
Current size C (UR)	20 A	Conductor size Factory wiring, max	12 AWG
Conductor size Factory wiring, min	22 AWG	Conductor size Field wiring, max	12 AWG

**IECEX/ATEX rating data**

Certificate no.	KEMA97ATEX1798U	ATEX certificate	KEMA97ATEX1798U_d.pdf
ATEX certificate	KEMA97ATEX1798U_e.pdf	Certificate no.	IECEXKEM06.0014U
max. voltage	550 V	Current (ATEX)	21 A
Conductor cross-section, max.	2 mm <sup>2</sup>	max. voltage	550 V
Current (IECEX)	21 A	Conductor cross-section, max.	2.5 mm <sup>2</sup>
Voltage when using cross-connections	CrossConnectionGuide.pdf	Operating temperature range	
Marking EN 60079-7	Ex e II		

**Additional technical data**

Colour of insulating material	blue	Connection direction	on side
End cover plate required	Yes	Explosion-tested version	Yes
Flammability class UL 94	V-2	Insulating material	PA 66
Levels cross-connected internally	No	No. of clamping points per level	2
Number of identical terminals	1	Number of levels	1
Open sides	right	Operating temperature range, max.	100 °C
Operating temperature range, min.	-50 °C	Product family	SAK terminal feed-through terminal
Type of connection	Screw connection	Type of mounting	Snap-on

**Conductors for clamping (additional connection)**

Rated current	24 A	Type of connection	Screw connection
Clamping screw	M 2.5	Blade size	0.6 x 3.5 mm
Tightening torque, max.	0.6 Nm	Tightening torque, min.	0.4 Nm
Conductor cross-section, flexible plus plastic collar DIN 46228/1, further connection, min.	0.5 mm <sup>2</sup>	Conductor cross-section, flexible plus plastic collar DIN 46228/1, further connection, max.	4 mm <sup>2</sup>
Conductor connection cross-section AWG, min.	AWG 26		

**SAK terminal feed-through terminal  
SAK 2.5/35 BL**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-2083  
www.weidmueller.com

**Technical data**

**Conductors for clamping (rated connection)**

Clamping range, min.	0.13 mm <sup>2</sup>	Clamping range, max.	6 mm <sup>2</sup>
Type of connection	Screw connection	Connection direction	on side
No. of connections	2	Stripping length	10 mm
Clamping screw	M 2.5	Blade size	0.6 x 3.5 mm
Tightening torque, min.	0.4 Nm	Tightening torque, max.	0.6 Nm
Torque setting with DMS electric screwdriver 1		Gauge to IEC 60947-1	A3
Conductor cross-section, solid, min.	0.5 mm <sup>2</sup>	Conductor cross-section, solid, max.	6 mm <sup>2</sup>
Stranded, min.	0.5 mm <sup>2</sup>	Stranded, max.	4 mm <sup>2</sup>
Conductor cross-section, flexible, max.	4 mm <sup>2</sup>	Conductor cross-section, flexible plus plastic collar DIN 46228/1, rated connection, min.	0.5 mm <sup>2</sup>
Conductor cross-section, flexible plus plastic collar DIN 46228/1, rated connection, max.	4 mm <sup>2</sup>	Conductor cross-section, flexible AEH plus plastic collar DIN 46228/4, rated connection, min.	0.5 mm <sup>2</sup>
Conductor cross-section, flexible AEH plus plastic collar DIN 46228/4, rated connection, max.	4 mm <sup>2</sup>	Twin wire-end ferrule, min.	0.5 mm <sup>2</sup>
Twin wire-end ferrule, max.	1.5 mm <sup>2</sup>	Conductor connection cross-section AWG, min.	AWG 26

**Rating data**

Rated cross-section	2.5 mm <sup>2</sup>	Rated voltage	800 V
Rated impulse withstand voltage	8 kV	Rated current	24 A
Standards	IEC 60947-7-1	Current with max. conductor	41 A
Pollution severity	3		

**Approvals**

Approvals institutes  
BURVER; CSA; EXIKONF;  
GERMLLOYD; GOSTME25;  
IECEXKEM; KEMAATEX;  
KEMAKEUR; LLOYDSREG;  
MARITREG; UR; CE

**Classifications**

ETIM 2.0	EC000897	ETIM 3.0	EC000897
eClass 5.1	27-14-11-20	eClass 6.0	27-14-11-20