

GENERAL DESCRIPTION

The SGM2030 is a low power and low dropout voltage RF linear regulator. It is capable of supplying 300mA output current with typical dropout voltage of only 270mV. The operating input voltage range is from 2.5V to 5.5V. The fixed output voltage range is from 1.2V to 3.3V.

Other features include logic-controlled shutdown mode, output current limit and thermal shutdown protection.

The SGM2030 is available in a Green UTDFN-1.2x1.6-4L package. It operates over an operating temperature range of -40°C to +85°C.

FEATURES

- **Operating Input Voltage Range: 2.5V to 5.5V**
- **Fixed Output Voltages:**
1.2V, 1.5V, 1.8V, 2.5V, 2.6V, 2.8V, 2.85V, 3.0V, 3.3V
- **Output Voltage Accuracy: ±3% at +25°C**
- **Low Output Noise: 140µV_{RMS} (TYP)**
- **Low Dropout Voltage: 270mV (TYP) at 300mA**
- **High PSRR: 71dB (TYP) at 1kHz**
- **Shutdown Current: 0.01µA (TYP)**
- **Thermal Shutdown Protection**
- **Output Current Limit**
- **-40°C to +85°C Operating Temperature Range**
- **Available in a Green UTDFN-1.2x1.6-4L Package**

APPLICATIONS

- Modems
- MP3 Players
- Cellular Telephones
- PCMCIA Cards
- Palmtop Computers
- Portable Electronics

TYPICAL APPLICATION




Figure 1. Typical Application Circuit

SGM2030


PACKAGE/ORDERING INFORMATION

MODEL	V _{OUT} (V)	PACKAGE DESCRIPTION	SPECIFIED TEMPERATURE RANGE	ORDERING NUMBER	PACKAGE MARKING	PACKING OPTION
SGM2030-1.2	1.2V	UTDFN-1.2×1.6-4L	-40°C to +85°C	SGM2030-1.2YUDG4G/TR	63X	Tape and Reel, 5000
SGM2030-1.5	1.5V	UTDFN-1.2×1.6-4L	-40°C to +85°C	SGM2030-1.5YUDG4G/TR	9DX	Tape and Reel, 5000
SGM2030-1.8	1.8V	UTDFN-1.2×1.6-4L	-40°C to +85°C	SGM2030-1.8YUDG4G/TR	4EX	Tape and Reel, 5000
SGM2030-2.5	2.5V	UTDFN-1.2×1.6-4L	-40°C to +85°C	SGM2030-2.5YUDG4G/TR	9EX	Tape and Reel, 5000
SGM2030-2.6	2.6V	UTDFN-1.2×1.6-4L	-40°C to +85°C	SGM2030-2.6YUDG4G/TR	68X	Tape and Reel, 5000
SGM2030-2.8	2.8V	UTDFN-1.2×1.6-4L	-40°C to +85°C	SGM2030-2.8YUDG4G/TR	4FX	Tape and Reel, 5000
SGM2030-2.85	2.85V	UTDFN-1.2×1.6-4L	-40°C to +85°C	SGM2030-2.85YUDG4G/TR	BAX	Tape and Reel, 5000
SGM2030-3.0	3.0V	UTDFN-1.2×1.6-4L	-40°C to +85°C	SGM2030-3.0YUDG4G/TR	50X	Tape and Reel, 5000
SGM2030-3.3	3.3V	UTDFN-1.2×1.6-4L	-40°C to +85°C	SGM2030-3.3YUDG4G/TR	56X	Tape and Reel, 5000

Green (RoHS & HSF): SG Micro Corp defines "Green" to mean Pb-Free (RoHS compatible) and free of halogen substances. If you have additional comments or questions, please contact your SGMICRO representative directly.

ORDER NUMBER


SGM2030 - X X X G / TR



MARKING INFORMATION

NOTE: X = Date Code.

YY X



SGM2030

ABSOLUTE MAXIMUM RATINGS

IN to GND	-0.3V to 6V
Output Short-Circuit Duration.....	Infinite
EN to GND.....	-0.3V to V_{IN}
OUT to GND	-0.3V to $(V_{IN} + 0.3V)$
Package Thermal Resistance	
UTDFN-1.2×1.6-4L, θ_{JA}	148°C/W
Junction Temperature.....	+150°C
Storage Temperature Range	-65°C to +150°C
Lead Temperature (Soldering, 10s).....	+260°C
ESD Susceptibility	
HBM.....	4000V
MM.....	400V

RECOMMENDED OPERATING CONDITIONS

Operating Temperature Range	-40°C to +85°C
-----------------------------------	----------------

OVERSTRESS CAUTION

Stresses beyond those listed in Absolute Maximum Ratings may cause permanent damage to the device. Exposure to absolute maximum rating conditions for extended periods may affect reliability. Functional operation of the device at any conditions beyond those indicated in the Recommended Operating Conditions section is not implied.


ESD SENSITIVITY CAUTION

This integrated circuit can be damaged if ESD protections are not considered carefully. SGMICRO recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage. ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because even small parametric changes could cause the device not to meet the published specifications.

DISCLAIMER

SG Micro Corp reserves the right to make any change in circuit design, or specifications without prior notice.

PIN CONFIGURATION



PIN DESCRIPTION

PIN	NAME	FUNCTION
1	IN	Input Voltage Supply Pin. It is recommended to use a 1µF or larger ceramic capacitor from IN pin to ground.
2	GND	Ground.
3	EN	Enable Pin. Drive EN high to turn on the regulator. Drive EN low to turn off the regulator.
4	OUT	Regulator Output Voltage Pin. It is recommended to use 1µF or larger ceramic output capacitor from OUT pin to ground. The capacitor should be located very close to this pin.
Exposed Pad	NC	No Connection.

ELECTRICAL CHARACTERISTICS

(V_{IN} = V_{OUT (NOMINAL)} + 0.5V⁽¹⁾, Full = -40°C to +85°C, unless otherwise noted.)







PARAMETER	SYMBOL	CONDITIONS	TEMP	MIN	TYP	MAX	UNITS	
Input Voltage	V _{IN}		+25°C	2.5		5.5	V	
Output Voltage Accuracy ⁽¹⁾		I _{OUT} = 0.1mA	+25°C	-3		+3	%	
Maximum Output Current ⁽¹⁾			+25°C	300			mA	
Output Current Limit ⁽¹⁾	I _{LIMIT}		+25°C	310			mA	
Ground Pin Current	I _Q	No load, EN = 2V	+25°C		95	200	μA	
Dropout Voltage ⁽²⁾		I _{OUT} = 1mA	+25°C		0.9		mV	
		I _{OUT} = 300mA			270	400		
Line Regulation ⁽¹⁾	ΔV _{LNR}	V _{IN} = 2.5V or (V _{OUT} + 0.5V) to 5.5V, I _{OUT} = 1mA	+25°C		0.02	0.05	%/V	
Load Regulation	ΔV _{LDR}	I _{OUT} = 0.1mA to 300mA, C _{OUT} = 1μF, V _{OUT} > 2V	+25°C		0.002	0.005	%mA	
		I _{OUT} = 0.1mA to 300mA, C _{OUT} = 1μF, V _{OUT} ≤ 2V			0.004	0.008		
Output Voltage Noise	e _n	f = 10Hz to 100kHz, C _{OUT} = 10μF	+25°C		140		μV _{RMS}	
Power Supply Rejection Ratio	PSRR	I _{OUT} = 50mA, C _{OUT} = 1μF, V _{IN} = V _{OUT} + 1V	f = 217Hz	+25°C		72		dB
			f = 1kHz	+25°C		71		dB
Shutdown⁽³⁾								
EN Input Threshold	V _{IH}	V _{IN} = 2.5V to 5.5V, V _{EN} = -0.3V to V _{IN}	Full		1.5		V	
	V _{IL}		Full			0.3		
EN Input Bias Current	I _{B(SHDN)}	EN = 0V and EN = 5.5V	+25°C		0.01	1	μA	
			Full		0.01			
Shutdown Supply Current	I _{Q(SHDN)}	EN = 0.4V	+25°C		0.01	1	μA	
			Full		0.01			
Shutdown Exit Delay ⁽⁴⁾		C _{OUT} = 1μF, No Load	+25°C		10		μs	
Thermal Protection								
Thermal Shutdown Temperature	T _{SHDN}				150		°C	
Thermal Shutdown Hysteresis	ΔT _{SHDN}				15		°C	

NOTES:

- V_{IN} = V_{OUT (NOMINAL)} + 0.5V or 2.5V, whichever is greater.
- The dropout voltage is defined as V_{IN} - V_{OUT}, when V_{OUT} is 100mV below the value of V_{OUT} for V_{IN} = V_{OUT} + 0.5V.
(Only applicable for V_{OUT} = +2.5V to +5.0V.)
- V_{EN} = -0.3V to V_{IN}
- Time needed for V_{OUT} to reach 90% of final value.







TYPICAL PERFORMANCE CHARACTERISTICS

$V_{IN} = V_{OUT (NOMINAL)} + 0.5V$ or $2.5V$ (whichever is greater), $C_{IN} = 1\mu F$, $C_{OUT} = 1\mu F$, $T_A = +25^\circ C$, unless otherwise noted.



TYPICAL PERFORMANCE CHARACTERISTICS (continued)


$V_{IN} = V_{OUT(NOMINAL)} + 0.5V$ or $2.5V$ (whichever is greater), $C_{IN} = 1\mu F$, $C_{OUT} = 1\mu F$, $T_A = +25^\circ C$, unless otherwise noted.




TYPICAL PERFORMANCE CHARACTERISTICS (continued)

$V_{IN} = V_{OUT (NOMINAL)} + 0.5V$ or $2.5V$ (whichever is greater), $C_{IN} = 1\mu F$, $C_{OUT} = 1\mu F$, $T_A = +25^\circ C$, unless otherwise noted.


Line-Transient Response



Shutdown Exit Delay



Output Noise 10Hz to 100kHz



APPLICATION INFORMATION

The SGM2030 is a low power and low dropout LDO and provides 300mA output current. These features make the device a reliable solution to solve many challenging problems in the generation of clean and accurate power supply. The high performance also makes the SGM2030 useful in a variety of applications. The SGM2030 provides protection functions for output overload, output short-circuit condition and overheating.

Input Capacitor Selection (C_{IN})

The input decoupling capacitor is necessary to be connected as close as possible to the IN pin for ensuring the device stability. 1 μ F or larger X7R or X5R ceramic capacitor is selected to get good dynamic performance.

When V_{IN} is required to provide large current instantaneously, a large effective input capacitor is required. Multiple input capacitors can limit the input tracking inductance. Adding more input capacitors is available to restrict the ringing and to keep it below the device absolute maximum ratings.

Output Capacitor Selection (C_{OUT})

The output decoupling capacitor should be located as close as possible to the OUT pin. 1 μ F or larger X7R or X5R ceramic capacitor is selected to get good dynamic performance. The minimum effective capacitance of C_{OUT} that SGM2030 can remain stable is 0.5 μ F. For ceramic capacitor, temperature, DC bias and package size will change the effective capacitance, so enough margin of C_{OUT} must be considered in design. Larger capacitance and lower ESR C_{OUT} will help improve the

load transient response and increase the high frequency PSRR.

Enable Control

The SGM2030 uses the EN pin to enable/disable its device.

When the EN pin voltage is lower than 0.3V, the device is in shutdown state.

When the EN pin voltage is higher than 1.5V, the device is in active state. The output voltage is regulated to expected value.

Output Current Limit and Short-Circuit Protection

When overload events happen, the output current is internally limited to 310mA (MIN). When the OUT pin is shorted to ground, the short-circuit protection will limit the output current.

Thermal Shutdown

The SGM2030 can detect the temperature of die. When the die temperature exceeds the threshold value of thermal shutdown, the SGM2030 will be in shutdown state and it will remain in this state until the die temperature decreases to +135°C.

Layout Guidelines

To get good PSRR, low output noise and high transient response performance, the input and output bypass capacitors must be placed as close as possible to the IN pin and OUT pin separately. V_{IN} and V_{OUT} had better use separate ground planes and these ground planes are single point connected to the GND pin.



REVISION HISTORY

NOTE: Page numbers for previous revisions may differ from page numbers in the current version.

MAY 2016 – REV.A.4 to REV.B	Page
Changed Normalized Output Voltage vs. Temperature	6
AUGUST 2014 – REV.A.3 to REV.A.4	Page
Changed TYPICAL PERFORMANCE CHARACTERISTICS section	7

PACKAGE OUTLINE DIMENSIONS

UTDFN-1.2×1.6-4L



RECOMMENDED LAND PATTERN (Unit: mm)

Symbol	Dimensions In Millimeters		
	MIN	MOD	MAX
A	0.500	0.550	0.600
A1	0.000		0.050
A2	0.152 REF		
D	1.150	1.200	1.250
D1	0.810	0.860	0.910
E	1.550	1.600	1.650
E1	0.450	0.500	0.550
b	0.200	0.250	0.300
e	0.500 BSC		
L	0.300	0.350	0.400

PACKAGE INFORMATION

TAPE AND REEL INFORMATION

REEL DIMENSIONS



TAPE DIMENSIONS



NOTE: The picture is only for reference. Please make the object as the standard.

KEY PARAMETER LIST OF TAPE AND REEL

Package Type	Reel Diameter	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P0 (mm)	P1 (mm)	P2 (mm)	W (mm)	Pin1 Quadrant
UTDFN-1.2×1.6-4L	7"	9.0	1.50	1.70	0.60	4.0	4.0	2.0	8.0	Q2

000001

PACKAGE INFORMATION

CARTON BOX DIMENSIONS



NOTE: The picture is only for reference. Please make the object as the standard.

KEY PARAMETER LIST OF CARTON BOX

Reel Type	Length (mm)	Width (mm)	Height (mm)	Pizza/Carton
7" (Option)	368	227	224	8
7"	442	410	224	18

DD0002