


Actuator

704.209.7

Distribution by
DigiKey

DigiKey



<https://digikey.eao.com/p/704.209.7>

Your product:



704.209.7 Actuator

FRONT

Front bezel material:	Plastic
Front form:	square
Front bezel colour:	Black
Front dimension:	30 mm x 30 mm

MOUNTING

Design:	raised
----------------	--------

OPERATING-/INDICATION PART

Lens illumination:	non illuminative
Lens material:	Plastic
Lens shape:	flush
Lens optics:	transparent
Lens colour:	Colourless

ELECTRICAL CHARACTERISTICS

Standards:	The switches comply with the "Standards for low-voltage switching devices" DIN EN 60947-1
-------------------	---

MECHANICAL CHARACTERISTIC

Weight:	0.04 kg
Operating force:	6.2 N
Mechanical lifetime:	≤3 Mio. cycles of operation

Operating Travel: ca. 5.8 mm ± 0.2 mm

Switching action: Momentary

AMBIENT CONDITION

Storage temperature: - 40 °C ... + 85 °C

IP Protection: IP65 front side

Operating temperature: - 40 °C ... + 55 °C

OTHER

max. number of switching elements: 3


Housing colour: Black

Short Description: Actuator, 30 mm x 30 mm, flush, non illuminative, Colourless, Plastic, transparent, square, Black, Plastic, Momentary

Hints: Frontring with protective cover to be mounted with a torque of 0.4 Nm onto actuator,Max. 3 switching elements can be clipped on


Housing material: Plastic

Mounting cut-outs:



A = Screw terminal
 B = Push-in terminal (PIT)
 C = Plug-in terminal 6.3 mm x 0.8 mm
 D = Double plug-in terminal 6.3 mm x 0.8 mm

Wiring diagrams:



Dimension drawings:

A = Screw terminal

