



Innovative Technology for a Connected World



Laird Technologies' Fabric-over-foam (FoF) 51H EMI gaskets provide excellent EMI shielding performance for customers where EMI issues occur. The 51H series EMI gaskets are composed of electrically conductive fabric wrapped around a soft urethane foam core. They are supplied with either a conductive or non-conductive pressure sensitive adhesive (PSA), and can be equipped with an Extended Release Liner (ERL) on the adhesive. The 51H is a halogen-free, UL 94V0 rated product that can be created with cross-section profiles such as rectangle, D, C, P, T, knife, bell shapes, and others. The 51H EMI gaskets can be further customized to an application by die-cutting, hole punching, notching, etc.


FEATURES **VROHS**

- Fabric-over-Foam gaskets are RoHS compliant
- Halogen-free per IEC-61249-2-21 standard
- UL 94V0
- Low surface resistivity of < 0.07 Ω/□ provides excellent conductivity
- Shielding effectiveness of >100 dB across a wide spectrum of frequencies
- Extremely low compression forces allow for use of lighter materials
- Fabric is highly conductive to provide good EMI shielding and grounding
- Abrasion resistant metallized fabrics show virtually no degradation in electrical performance after 1,000,000 cycles
- Laird Technologies' proprietary coating prevents fabric fraying and fingerprinting
- Available with conductive or non-conductive PSA
- Many cross-section profiles available such as rectangle, D, C, P, T, knife, bell and more
- Profile gaskets can be cut to specified lengths, kiss-cut on release liner, or mitered to form frame configurations


MARKETS

- Cabinet applications
- LCD and Plasma TV
- Medical equipment
- Servers
- Printers
- Laptop computers
- Networking equipment
- Desktop computers
- Telecommunications cabinets

FORCE/DISPLACEMENT/RESISTANCE (FDR)



SHIELDING EFFECTIVENESS (dB)



global solutions: local support...

USA: +1.866.928.8181 Europe: +49.0.8031.2460.0 Asia: +86.755.2714.1166




Innovative **Technology** for a **Connected** World

51H EMI Gaskets Fabric-over-Foam

Item	Unit	Value	Test Method		
Shielding Effectiveness					
at 100 MHz		108	SAE-ARP-1705(Mod.)		
at 1 GHz	dB	110	(W10 mm x H8 mm)		
Surface Resistivity	Ω/\square	< 0.07	ASTM F390		
Compression Set	%	< 20	ASTM D3574		
Operation Temperature	°C	-40 ~ 70	-		
Flame Retardant	UL 94V0 (UL file No.E170327)				
Hazardous Substance	Compliant with RoHS (Directive 2011/65/EU)				
	Compliant with SONY ss-00259				
	Halogen-free (based on IEC-61249-2-21)				
	Antimony-free				
Shelf Life	12 months at 23°C/ 60% R.H.				

COMPOSITION OF PRODUCT




PRESSURE SENSITIVE ADHESIVE (PSA TAPE) OPTIONS

Name	Туре	Thickness (mm)	Peel strength on stainless steel (JIS Z 0237)	Z-axis Resistance
LT-301	Conductive PSA	0.09	> 1.3 kgf/25 mm	< 0.05 Ω
LT-350	PSA	0.12	> 2 kgf/25 mm	-

*Other PSA can be provided. Contact Laird Technologies engineering.

ORDERING INFORMATION

PART NUMBER EXAMPLE



EMI-DS-FOF-51H 0712

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user. Laird Technologies materials or products for any specific or general uses. Laird Technologies to incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2012 Laird Technologies, Inc. All Rights Reserved. Laird Technologies Logo, and other marks are tadde marks or registered trade marks or Laird Technologies, Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Laird Performance Materials:

4046-AG-51H-01800 4049-AD-51H-01800 4053-AE-51H-01800 4056-AE-51H-01800 4078-AB-51H-01800 4084-AB-51H-01800 4096-AC-51H-01800 4105-AD-51H-01800 4131-AB-51H-01800 4184-AD-51H-01800 4202-AE-51H-01800 4209-AB-51H-01800 4212-AC-51H-01800 4220-AC-51H-01800 4245-AB-51H-01800 4379-AD-51H-01800 4520-AC-51H-01800 4609-AH-51H-01800 4633-AF-51H-01800 4692-AC-51H-01800 4701-AB-51H-01800 4742-AI-51H-01800 4788-AF-51H-01800 4789-AC-51H-01800 4882-AB-51H-01800 4056-PA-51H-01800 4692-PA-51H-01800 4701-PA-51H-01800 4084-PA-51H-01800 4049-PA-51H-01800 4053-PA-51H-01800 4209-PA-51H-01800 4742-PA-51H-01800 4202-PA-51H-01800 4245-PA-51H-01800 4096-PA-51H-01800 4220-PA-51H-01800 4212-PA-51H-01800 4046-PA-51H-01800 4105-PA-51H-01800 4789-PA-51H-01800 4078-PA-51H-01800 4520-PA-51H-01800 4788-PA-51H-01800 4131-PA-51H-01800 4882-PA-51H-01800 4184-PA-51H-01800 4379-PA-51H-01800 4633-PA-51H-01800 4548-PA-51H-01800 4795PA51H09600 4157PA51H01800 4049PA51H00165 4299-PA-51H-01800 4789PA51H09600 4212PA51H00570 4204PA51H01200 4594-PA-51H-01800 4240-PA-51H-01800 4609-PA-51H-01800 4064PA51H07200 4787PA51H09600 4120PA51H07200 4228PA51H01520 4120PA51H01800 4208PA51H01800 4787PA51H01800 4231PA51H01800 4047PA51H01800 4215PA51H01800 4519PA51H01800 4176PA51H01800 4688PA51H01800 4609PA51H00818 4094PA51H01134 4795PA51H01800 4082PA51H01800 4797PA51H01800 4357PA51H01800 4211PA51H01800 4186PA51H01800 4246PA51H01800 4A58PA51H01800 4090PA51H01800 4283pa51h01800 4181PA51H01800 4584PA51H01800 4609PA51H09600 4078PA51H04800 4541AB51H00100 4J68EF51H00650 4060PA51H09600 4062PA51H09600 4212PC51H00240 4212PC51H00291 4212PC51H01051 4212PC51H01450 4212PC51H01220 4212PC51H00287 4212PC51H01055