

ARCA 507030W



Sample photo

Order symbol: ARCA 507030W
Product nbr: 8120151
Description: Cabinet, PC
Remarks: Cover with window, 2-point locking

EAN: 6418074086068
EI. number:
 Finland: 3424070
 Electric No. 8212095465
 Denmark:
 Electric No. Sweden: 2500153

Including: Cabinet base, door with PUR gasket, mounting plate, screws for mounting plate. 3mm double bit lock(s) with key. S versions with swinghandle 2-point locking system. F versions with flange opening (including gasket and screws). Door guide included.

Dimensions:	Length	Width	Height	Accessories:
mm:	500	700	300	MPP ARCA 5070
inch:	19.7	27.6	11.8	MPMP ARCA 7050

Materials:

Material: Polycarbonate

Base colour: RAL 7035 -light grey

Cover colour: RAL 7035 -light grey

Gasket material: Polyurethane

Temperatures:

Temperature °C (short term): -40 ... 120 °C

Temperature °C (continuous): -40 ... 80 °C

Temperature °F (short term): -40 ... 250 °F

Temperature °F (continuous): -40 ... 175 °F

Accessories:

MPS ARCA 7050 Mounting plate (630x430x2 mm)

MPP ARCA 5070	Mounting plate perforated (630x430x2 mm - 26x11 mm)
MPMP ARCA 7050	Mounting plate multiperforated (630x430x2 mm - □3.6 mm)
MPX ARCA 7050	Mounting plate (630x430 mm)
DRS ARCA 507030	DIN rail frame set
IDS ARCA 5070	Inner door set
PMK ARCA 70	Pole mounting kit
RCS ARCA 5070	Rain canopy set
SBK ARCA 50	Support bar kit
SBK ARCA 70	Support bar kit
DSP ARCA LM	Door stopper ARCA, left, midsize, for 5070-8060
DSP ARCA RM	Door stopper ARCA, right, midsize for 5070-8060

Rating:

Ingress Protection (EN 60529): IP65
 Impact Resistance (EN 62262): IK08
 Electrical insulation: Totally insulated
 Halogen free (DIN/VDE 0472, Part 815): 1
 UV resistance: UL 508
 Flammability Rating: UL 94 5VA
 Glow Wire Test (IEC 695-2-1) °C: 960

Certificates:

SGS Fimko
 Gost R

