

Part Number : 351550300

**Product Description :** 2.50mm Pitch Wire-to-Board Housing, Positive Lock, Natural, 3

Circuits

Status: New Business Not Supported

Series Number: 35155

**Product Category:** Connector Housings

#### **Documents & Resources**

## **Product Environment Compliance**

## Compliance

| GADSL/IMDS         | Not Relevant                                       |
|--------------------|--|
| China RoHS         | <b>©</b>   |
| EU ELV             | Not Relevant                                       |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2-<br>21             |
| REACH SVHC         | Not Contained per D(2024)4144-DC<br>(27 June 2024) |
| EU RoHS            | Compliant per EU 2015/863                          |

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

## Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

#### **EU RoHS Certificate of Compliance**

#### **Part Details**

#### General

| Status   | New Business Not Supported |
|----------|----------------------------|
| Category | Connector Housings         |

| Series       | 35155  |
|--------------|--|
| Description  | 2.50mm Pitch Wire-to-Board<br>Housing, Positive Lock, Natural, 3<br>Circuits |
| Application  | Signal, Wire-to-Wire   |
| Product Name | N/A  |
| UPC          | 800753683914   |

## Agency

| CSA | LR19980 |
|-----|---------|
| UL  | E29179  |

# Physical

| Breakaway                     | No             |
|-------------------------------|----------------|
| Circuits (maximum)            | 3              |
| Color - Resin                 | Natural        |
| Flammability                  | 94V-0          |
| Gender                        | Receptacle     |
| Glow-Wire Capable             | No             |
| Keying to Mating Part         | None           |
| Lock to Mating Part           | Yes            |
| Material - Resin              | Polyester      |
| Net Weight                    | 0.386/g        |
| Number of Rows                | 1              |
| Packaging Type                | Bag            |
| Panel Mount                   | No             |
| Pitch - Mating Interface      | 2.50mm         |
| Pitch - Termination Interface | 2.50mm         |
| Temperature Range - Operating | -40° to +105°C |