

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION  
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

| LOC |    | DIST |     | REVISIONS                 |         |     |      |
|-----|----|------|-----|---------------------------|---------|-----|------|
| DF  | DO | P    | LTR | DESCRIPTION               | DATE    | DWN | APVD |
|     |    | N1   |     | REVISED PER ECO-11-005139 | 21MAR11 | RK  | HMR  |



| SIZE | B DIM | C DIM<br>±.0050 | (L DIM) |
|------|-------|-----------------|---------|
| 09   | .229  | .3085           | (.100)  |
| 15   | .304  | .3835           | (.175)  |
| 25   | .429  | .5085           | (.300)  |
| 37   | .579  | .6585           | (.450)  |
| 51   | .754  | .8335           | (.625)  |
| 65   | .929  | 1.0085          | (.800)  |

- 1. SHELL OPTIONS (TO BE SPECIFIED IN NANONICS PART NUMBER):  
 METAL: 6061-T6 ALUMINUM, ELECTROLESS NICKEL PLATED PER MIL-C-26074 (STANDARD) OR GOLD PLATED PER MIL-G-45204  
 303 STAINLESS STEEL, PASSIVATED PER SAE-AMS-QQ-P-35  
 INSULATOR MATERIAL FOR ALL METAL SHELLS IS LIQUID CRYSTAL POLYMER (LCP) PER MIL-M-24519 OR PER ASTM D5138  
 PLASTIC: LIQUID CRYSTAL POLYMER (LCP) PER MIL-M-24519 OR PER ASTM D5138
- 2. STANDARD 1.0 X 0.25mm MOUNTING AND JACKSCREW THREADS ARE SHOWN FOR REFERENCE ONLY AND MUST BE SPECIFIED IN THE NANONICS PART NUMBER WHEN REQUIRED. 1.2 X 0.25mm THREADS ALSO AVAILABLE.
- 3. MOUNTING HARDWARE IS AVAILABLE WITH THIS CONFIGURATION (NOT SHOWN). HARDWARE MUST BE SPECIFIED IN THE NANONICS PART NUMBER. CONSULT TE CONNECTIVITY FOR DETAILS.
- 4. THIS CONFIGURATION MAY BE TERMINATED WITH 28 AWG SOLID, 30 AWG STRANDED OR SMALLER WIRE, OR RIBBON CABLE. CONDUCTOR TYPE AND LENGTH MUST BE SPECIFIED IN NANONICS PART NUMBER.
- 5. THIS DRAWING PREVIOUSLY IDENTIFIED AS NANONICS N10138/202

|   |   |                               |   |                         |       |   |   |       |   |      |       |   |      |       |   |   |        |   |    |                   |            |                    |
|---|---|-------------------------------|---|-------------------------|-------|---|---|-------|---|------|-------|---|------|-------|---|---|--------|---|----|-------------------|------------|--------------------|
| THIS DRAWING IS A CONTROLLED DOCUMENT.  |   | DWN<br>D. RYAN<br>21 APR 92   |   |                         |       |   |   |       |   |      |       |   |      |       |   |   |        |   |    |                   |            |                    |
| DIMENSIONS: INCHES  |   | CHK<br>E. PAULUS<br>15 MAY 98 |   |                         |       |   |   |       |   |      |       |   |      |       |   |   |        |   |    |                   |            |                    |
| TOLERANCES UNLESS OTHERWISE SPECIFIED:  |   | APVD<br>M. STORRY<br>5 APR 01 | NAME<br>RECEPTACLE ASSEMBLY, FLYING LEADS,<br>TWO ROW DUALLOBE,<br>PLASTIC OR METAL |                         |       |   |   |       |   |      |       |   |      |       |   |   |        |   |    |                   |            |                    |
| <table border="1"> <tr><td>0 PLC</td><td>±</td><td>-</td></tr> <tr><td>1 PLC</td><td>±</td><td>-</td></tr> <tr><td>2 PLC</td><td>±</td><td>.010</td></tr> <tr><td>3 PLC</td><td>±</td><td>.005</td></tr> <tr><td>4 PLC</td><td>±</td><td>-</td></tr> <tr><td>ANGLES</td><td>±</td><td>1°</td></tr> </table> |   | 0 PLC                         | ±   | -                       | 1 PLC | ± | - | 2 PLC | ± | .010 | 3 PLC | ± | .005 | 4 PLC | ± | - | ANGLES | ± | 1° | PRODUCT SPEC<br>- | SIZE<br>A2 | CAGE CODE<br>00779 |
| 0 PLC   | ± | -                             |   |                         |       |   |   |       |   |      |       |   |      |       |   |   |        |   |    |                   |            |                    |
| 1 PLC   | ± | -                             |   |                         |       |   |   |       |   |      |       |   |      |       |   |   |        |   |    |                   |            |                    |
| 2 PLC   | ± | .010                          |   |                         |       |   |   |       |   |      |       |   |      |       |   |   |        |   |    |                   |            |                    |
| 3 PLC   | ± | .005                          |   |                         |       |   |   |       |   |      |       |   |      |       |   |   |        |   |    |                   |            |                    |
| 4 PLC   | ± | -                             |   |                         |       |   |   |       |   |      |       |   |      |       |   |   |        |   |    |                   |            |                    |
| ANGLES  | ± | 1°                            |   |                         |       |   |   |       |   |      |       |   |      |       |   |   |        |   |    |                   |            |                    |
| MATERIAL<br>SEE NOTES   |   | FINISH<br>SEE NOTES           | WEIGHT<br>-   | DRAWING NO<br>C=1589476 |       |   |   |       |   |      |       |   |      |       |   |   |        |   |    |                   |            |                    |
|   |   | CUSTOMER DRAWING              | SCALE<br>8:1  | SHEET<br>1 of 1         |       |   |   |       |   |      |       |   |      |       |   |   |        |   |    |                   |            |                    |
|   |   |                               | RESTRICTED TO<br>-  | REV<br>N1               |       |   |   |       |   |      |       |   |      |       |   |   |        |   |    |                   |            |                    |

1589476

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[STM015SC2DX010N](#)