

HX-CT

TE Internal #: ER4009-000

Continuous, Low Fire Hazard, 2:1 Shrink Ratio, Black, 9.5mm [.375in]

Expanded Inside Diameter, HX-CT, Printable Tubing

View on TE.com >



Identification & Labeling > Printable Tubing > Continuous Tube, Low Fire Hazard HX-CT



Printable Tubing Type: Continuous

Printable Tubing Grade: Low Fire Hazard

Shrink Ratio: 2:1

Primary Product Color: Black

Expanded Inside Diameter (Min): 9.5 mm [.375 in]

All Continuous Tube, Low Fire Hazard HX-CT (27)

Features

Product Type Features

Printable Tubing Type	Continuous
Printable Tubing Grade	Low Fire Hazard
Body Features	
Shrink Ratio	2:1
Primary Product Color	Black
Dimensions	
Expanded Inside Diameter (Min)	9.5 mm[.375 in]
Recovered Inside Diameter (Max)	4.8 mm[.189 in]
Compatible Cable Diameter Range	4.75 – 7.6 mm[.187 – .299 in]
Usage Conditions	
Operating Temperature Range	-40 - 105 °C[-40 - 221 °F]
Printer/Label Features	
Printer Technology	Thermal Transfer
Packaging Features	

50

Packaging Quantity



Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts






















Also in the Series | HX-CT



Documents

Product Drawings

HX-CT-50M-9.5-OUT-0

English

Datasheets & Catalog Pages

Printable Continuous Tubing

English

HX-CT, Low Fire Hazard Continuous Heat Shrink Identification Tube

English

Cable Identification Product Shelf Life

English

Product Specifications

Product Specification

English

Instruction Sheets

Continuous, Low Fire Hazard, 2:1 Shrink Ratio, Black, 9.5mm [.375in] Expanded Inside Diameter, HX-CT, Printable Tubing



Instruction Sheet (non U.S.)

English