



# 8-Outlet Surge Protector with 2 USB Ports (2.1A Shared) - 8 ft. (2.43 m) Cord, 1200 Joules, Tel/Modem, Black

MODEL NUMBER: TLP88TUSBB











8-outlet surge protector safeguards your home/office electronics against dangerous surges, spikes and line noise.

#### **Features**

8-Outlet Surge Protector with USB Safeguards Your Sensitive Electronics Ideal for your home or office workstation, this Protect It!® 8-outlet surge protector features a surge protection rating of 1200 joules to defend your sensitive electronic components against strong power surges and spikes. Because residential power outlets have three wires—hot line (H), neutral (N) and ground (G)—the TLP88TUSBB protects all three, covering the two protection modes: full normal mode (H-N) and common mode (N-G/H-G).

**NEMA 5-15R Outlets Accept a Wide Range of Electronic Devices**Plug your PC, printer, wireless router, game console, television, sound system or other home/office electronics into eight NEMA 5-15R outlets to protect them against dangerous surges, spikes and line noise. Three outlets are widely spaced to accommodate bulky power transformers without blocking adjacent outlets. Built-in safety covers prevent dust and debris from falling into unused outlets.

**RJ11 Cable Surge Protection Covers All Your Bases**Built-in RJ11 jacks allow connection of telephone, fax and modem equipment. The TLP88TUSBB prevents dangerous "back door" power surges from damaging your data line components.

2 USB Ports Share 2.1 Amps of Charging PowerThis surge protector with 2 USB ports is ideal for keeping your devices at full capacity. Two USB-A ports are available for charging your smartphone, tablet and other USB mobile devices.

Premium Protection from EMI/RFI Line Noise Helps Your Equipment Perform Better Various electromagnetic and radio sources found in virtually every home and business can cause disruptive interference on the AC line. Known as EMI (electromagnetic interference) and RFI (radio frequency interference), this line noise is a common cause of performance problems. This surge protector filters out disruptive line noise that can disturb your electronics and inflict hardware damage or data loss. This EMI/RFI filtering also helps your connected components perform better and last longer.

**Includes the Latest Safety Features**The lighted on/off switch provides one-touch control over connected equipment. A green LED confirms your connected equipment is protected.

Versatile Surge Protector Provides Multiple Installation OptionsThis surge protector with 8-ft. (2.43

### **Highlights**

- 8 NEMA 5-15R outlets distribute AC power to connected home/office equipment
- 1200 joules protect your valuable electronics against dangerous surges and spikes
- 2 USB ports share 2.1A for fast charging of phones, tablets and other mobile devices
- 8-ft. (2.43 m) cord with NEMA 5-15P plug allows flexibility in placing devices away from AC outlet
- RJ11 cable connectors offer surge protection to phone/fax/modem equipment

#### **Applications**

- Protect computers, peripherals, home theater equipment and other valuable electronics against AC power surges and spikes
- Filter potentially damaging line noise to improve connected equipment's performance and lifespan
- Safeguard valuable data against corruption stemming from unexpected surges
- Charge smartphones, tablets or other USB devices via USB ports

#### **Package Includes**

- TLP88TUSBB Protect It! 8-Outlet Surge Protector, Black
- · Owner's manual





m) cord and space-saving right-angle NEMA 5-15P plug helps you connect to a wall outlet located behind furniture placed flush against the wall. Keyhole slots incorporated into the bottom panel provide convenient wall or desk mounting options for the black plastic housing.

## **Specifications**

| OVERVIEW                           |   |  |
|------------------------------------|---|--|
| UPC Code                           | 037332223579  |  |
| Product Type                       | Surge Protector   |  |
| Charging Form Factor               | Strip   |  |
| Device Compatibility               | Phone; Tablet; Amazon Kindle                              |  |
| INPUT                              |   |  |
| Nominal Input Voltage(s) Supported | 120V AC   |  |
| Recommended Electrical Service     | 120V (110-125V)   |  |
| Input Plug Features                | Right Angle   |  |
| Input Cord Gauge Type              | 14 gauge; SJT   |  |
| Input Cord Gauge (AWG)             | 14  |  |
| Voltage Compatibility (VAC)        | 120   |  |
| Maximum Surge Amps                 | 35500   |  |
| Input Plug Type                    | NEMA 5-15P  |  |
| Input Cord Details                 | SJT   |  |
| Input Cord Length (ft.)            | 8   |  |
| Right-Angle Plug                   | Yes   |  |
| Input Cord Length (m)              | 2.44  |  |
| Integrated Cord Clip               | No  |  |
| OUTPUT                             |   |  |
| Frequency Compatibility            | 50 / 60 Hz  |  |
| Output Receptacles                 | (8) 5-15R   |  |
| Circuit Breaker (amps)             | 15  |  |
| Overload Protection                | 15A resettable illuminated combo switch / circuit breaker |  |
| Transformer Accommodation          | (6) Yes   |  |
| Outlet Orientation                 | Double row of 8 outlets total                             |  |
| Right-Angle Outlets                | Yes   |  |
| USER INTERFACE, ALERTS & CONTROLS  |   |  |
| Diagnostic LED(s)                  | Yes   |  |





| Switches                         | Combination AC circuit breaker and 2 position red illuminated on/off power switch |  |
|----------------------------------|---|--|
| Diagnostic LED Details           | Built-in LED confirms suppressor "protection present" (green) status              |  |
| -                                |   |  |
| CHARGING                         |   |  |
| Number of Charging Ports         | 2   |  |
| Total Charging Watts             | 10.5  |  |
| Charging Method                  | USB   |  |
| Charging Port Type               | USB A (FEMALE)  |  |
| Charging Ports / Amps            | (2) 2.1A  |  |
| Overcharge Protection            | No  |  |
| SURGE / NOISE SUPPRESSION        |   |  |
| AC Suppression Joule Rating      | 1200  |  |
| AC Suppression Response Time     | < 1 ns  |  |
| Protection Modes                 | Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression      |  |
| UL1449 Let Through Rating        | 500,500,500   |  |
| EMI / RFI Filtering              | Yes   |  |
| Automatic Shut-Off               | No  |  |
| DATALINE SURGE SUPPRESSION       |   |  |
| Telephone/DSL Protection Details | 1 line in/2 line out  |  |
| Cable (Coax) Protection          | No  |  |
| Network (Ethernet) Protection    | No  |  |
| Telephone/DSL Protection         | Yes   |  |
|                                  |   |  |
| PHYSICAL                         |   |  |
| Material of Construction         | Plastic   |  |
| Power Cord Color                 | Black   |  |
| Housing Color                    | Black   |  |
| Mounting Holes or Slots          | Yes   |  |
| Receptacle Color                 | Black   |  |
| Shipping Dimensions (hwd / in.)  | 11.02 x 7.09 x 1.50   |  |
| Shipping Weight (kg)             | 0.85  |  |
| Unit Dimensions (hwd / in.)      | 9.100 x 3.780 x 1.300   |  |
| Unit Dimensions (hwd / cm)       | 23.11 x 9.60 x 3.30   |  |
| Unit Weight (lbs.)               | 1.46  |  |
| Unit Weight (kg)                 | 0.66  |  |
|                                  |   |  |





| FEATURES & SPECIFICATIONS                                  |   |  |
|--|---|--|
| Rotatable Outlets  | No  |  |
| Antimicrobial  | No  |  |
| GaN Technology   | No  |  |
| STANDARDS & COMPLIANCE                                     |   |  |
| Product Certifications                                     | CAN/CSA-C22.2 No. 308 (Canada); cUL Listed; NOM (Mexico); UL 1449; UL 497A; UL 1363; UL Listed                          |  |
| Product Compliance   | FCC Part 68; RoHS   |  |
| WARRANTY & SUPPORT   |   |  |
| Product Warranty Period (Worldwide)                        | Lifetime limited warranty   |  |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$75,000 <a class="insuranceLink" href="//tripplite.eaton.com/support/insurance-policy">Ultimate Lifetime Insurance</a> |  |

1000 Eaton Boulevard Cleveland, OH 44122 United States https://tripplite.eaton.com © 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark. All other trademarks are the property of their respective owners.