



Heyco® Straight-Thru Strain Relief Bushings

For Round Cables




| WILL FIT THESE CABLES | | | | PANEL DIMENSIONS | | | | | | PART NO. | | DESCRIPTION | C Body Length | | | |
|------------------------------|------------------------------|----------------------|---------------|----------------------|------|-----------------------|------|--------------------------------------|------|----------|-------|-------------|---------------|---------|------|------|
| UL Type Designation | AWG/ Conductors | Approximate Diameter | | A Mounting Hole Dia. | | B To Prevent Rotation | | Maximum Panel Thickness ¹ | | Black | White | | in. | mm. | | |
| | | in. | mm. | in. | mm. | in. | mm. | in. | mm. | | | | | | | |
| SJ, SJT & SJO | 16/2 | .325 | 8,3 | .875 | 22,2 | .770 | 19,6 | .125 | 3,2 | 1240 | 1241 | SR 7K-2 | .750 | 19,1 | | |
| | 18/3 | .330 | 8,4 | | | | | | | | | | | | | |
| | 14/2 | .350 | 8,9 | | | | | | | | | | | | | |
| | 16/3 | .355 | 9,0 | | | | | | | | | | | | | |
| | 18/4 | .360 | 9,1 | | | | | | | | | | | | | |
| Same as SR 7K-2 above except | | | | See Schematic | | | | | | 1271 | 1272 | SR 7KR-2 | .750 | 19,1 | | |
| SJT | 18/4 | .360 | 9,1 | .750 | 19,0 | | | | | | | SR 7N-2 | .750 | 19,1 | | |
| | 14/3 | .370 | 9,4 | | | | | | | | | | | | | |
| S & ST | 18/2 | .390 | 9,9 | .750 | 19,0 | | .660 | 16,8 | .062 | 1,6 | 1244 | 1245 | SR 7N-2 | .750 | 19,1 | |
| | 18/3 | .405 | 10,3 | | | | | | | | | | | | | |
| | 16/2 | .405 | 10,3 | | | | | | | | | | | | | |
| | 16/3 | .430 | 10,9 | | | | | | | | | | | | | |
| Same as SR 7N-2 above except | | | | | | | | | | .125 | 3,2 | 1237 | 1238 | SR 7P-2 | .750 | 19,1 |
| SJT | 14/3 | .370 | 9,4 | | | | | | | | | SR 7W-2 | .750 | 19,1 | | |
| | 12/3 | .425 | 10,8 | | | | | | | | | | | | | |
| S & ST | 18/2 | .390 | 9,9 | .875 | 22,2 | .770 | 19,6 | .125 | 3,2 | 1247 | 1248 | SR 7W-2 | .750 | 19,1 | | |
| | 18/3 | .405 | 10,3 | | | | | | | | | | | | | |
| | 16/2 | .405 | 10,3 | | | | | | | | | | | | | |
| | 16/3 | .430 | 10,9 | | | | | | | | | | | | | |
| Same as SR 7W-2 above except | | | | | | | | | | .200 | 5,1 | 1250 | 1251 | SR 7L-2 | .750 | 19,1 |
| SJT | 12/3 | .425- .475 | 10,8- 12,1 | .875 | 22,2 | .840 | 21,3 | .125 | 3,2 | 1497 | 1498 | SR 31-2 | .812 | 20,6 | | |
| | 14/2 | .530 | 13,5 | | | | | | | | | | | | | |
| S & ST | 14/3 | .560 | 14,2 | .875 | 22,2 | .840 | 21,3 | .062 | 1,6 | 1254 | 1255 | SR 8N-2 | .828 | 21,0 | | |
| | 12/2 | .600 | 15,3 | | | | | | | | | | | | | |
| | Same as SR 8N-2 above except | | | | | | | | | | | | | | | |
| S | 12/2 | .600 | 15,2 | 1.093 | 27,7 | 1.000 | 25,4 | .281 | 7,1 | 1287 | 1288 | SR 9P-2 | 1.00 | 25,4 | | |
| | 12/3 | .635 | 16,1 | 1.125 | 28,6 | | | | | | | | | | | |
| | 10/2 | .640 | 16,3 | 1.093 | 27,7 | | | | | | | | | | | |
| S, ST & SO | 10/3 | .690 | 17,5 | 1.187 | 28,6 | | | | | | | | | | | |

- Protects the lifeline of your electric/ electronic products by absorbing the forces of pull, push, and twist that may be exerted on the flexible power cord.
- Securely anchors, insulates, and protects cables at panel entry points.
- Sizes SR7 to SR9 for mounting hole diameters from .750 in to 1.187 in.
- Standardized design! Fill unneeded SR mounting holes with Heyco Double D Holes.
- Sizes for narrow .062" (1,6mm) panel available:
SR 7N-2
SR 8N-2
See chart for details.
See pages 2-24, 2-25, and 2-26 for assembly tools and SR hole punches.


LabKit No. 1 (Part #1999)
Provides a working assortment for prototype and laboratory use. 180 assorted Heyco Strain Reliefs are identified in a handy compartmentalized plastic box. Ideal for design engineering groups. Details on page 2-27.

- See page 2-11 for Quick Specs.


Standard Colors: Black or White. Consult factory for color matching, prices, and minimum order quantities.
¹Maximum Panel Thickness—Part has additional clearance.



FOR SR-7KR-2 ONLY



STANDARD MOUNTING HOLES



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Heyco:](#)

[1218](#) [1201](#) [1241](#)