



Part Number : [732511355](#)

Product Description : 50 Ohms, SMA Jack, Vertical, PCB SMT, Gold (Au) Body, with Pick-and-Place Polyimide Film, Tape and Reel (400 Pieces)

Series Number : 73251

Status : Active

Product Category : RF / Coaxial Connectors

Documents & Resources

Drawings

[Drawing 732511355_sd.pdf](#)

[Packaging Design Drawing SD-73251-135-PKG-001.pdf](#)

3D Models and Design Files


[3D Model 732511355_stp.zip](#)

Specifications

[Product Specification PS-89675-346-001.pdf](#)

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Contains Lead per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant with Exemption 6(c) per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration

- IEC-62474

- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Active
Category	RF / Coaxial Connectors
Series	73251
Description	50 Ohms, SMA Jack, Vertical, PCB SMT, Gold (Au) Body, with Pick-and-Place Polyimide Film, Tape and Reel (400 Pieces)
Product Family	SMA RF Connectors
Product Name	SMA
Style	PCB
Type	Subminiature
UPC	887191360706

Electrical

Frequency	18 GHz
Impedance	50Ω
Power / Voltage	VOLTAGE: 500 Vrms@Sea Level

Physical

Gender	Jack
Keying to Mating Part	None
Net Weight	1.265/g
Orientation	Straight
Packaging Type	Embossed Tape on Reel
Panel Mount	No
Panel Mount Method	N/A
PCB Mounting	Surface Mount
Reverse Polar	No
Wire/Cable Type	N/A

Solder Process Data

Max-Duration	10
Lead-Free Process Capability	REFLOW
Max-Cycle	2
Max-Temp	260

This document was generated on Sep 18, 2024