

# MHM502-01A

In Production RoHS REACH

## Appearance & Shape



## Features

High Ozone Density

## Packaging Information

Packaging	Specifications	Minimum Order Quantity
-	Bulk(Bag)	102

### Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

# MHM502-01A

## Specifications

Input Voltage	12.0Vdc
Consumption Electricity	4.5W
Operating Temperature Range	-10°C to 50°C
Operating Humidity Range	20%RH to 90%RH
Ozone Amount	50.00mg/H
Max Operating Duty (%)	100
Lead Length	175mm

### Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.