



材料及电镀

1. 塑件主体: PA66,
2. 焊 针: 黄铜, 镀镍

电气性能

- 额定电压: 300V
- 额定电流: 8A
- 接触电阻: 20mΩ (Max)
- 绝缘电阻: 500MΩ\DC1000V
- 耐 电 压: AC1500V\1Min

机械性能

- 温度范围: -40℃ ~ +105℃
- 瞬时温度: +250℃ , 5秒

2	插针	铜	镀镍	
1	基座	PA66	绿色	
序号	品名	材质	电镀/颜色	备注

	深圳市虹成电子有限公司		品名 TITLE	接线端子																
			料号 PART NO	HC-JXDZRC-3.81-5P																
GENERAL TOLERANCES (UNLESS SPECIFIED)		比列 SCALE	1:1																	
		单位 UNIT	MM																	
公差参数		张数 PART NO	1 OF 1	制图 DRAW	AhYe															
<table border="1"> <tr> <th>Dim</th> <th>DimP</th> <th>DimL</th> </tr> <tr> <td>2-6P</td> <td>±0.10</td> <td>±0.20</td> </tr> <tr> <td>7-12P</td> <td>±0.20</td> <td>±0.30</td> </tr> <tr> <td>13-18P</td> <td>±0.25</td> <td>±0.40</td> </tr> <tr> <td>19-24P</td> <td>±0.30</td> <td>±0.50</td> </tr> </table>		Dim	DimP	DimL	2-6P	±0.10	±0.20	7-12P	±0.20	±0.30	13-18P	±0.25	±0.40	19-24P	±0.30	±0.50	版本 REV	A	审核 CHECKED	夏操云
Dim	DimP	DimL																		
2-6P	±0.10	±0.20																		
7-12P	±0.20	±0.30																		
13-18P	±0.25	±0.40																		
19-24P	±0.30	±0.50																		
<table border="1"> <tr> <td>X.xxx</td> <td>±0.15</td> </tr> <tr> <td>X.xx</td> <td>±0.25</td> </tr> <tr> <td>X.x</td> <td>±0.35</td> </tr> </table>		X.xxx	±0.15	X.xx	±0.25	X.x	±0.35	批准 APPROVE	赵亮亮											
X.xxx	±0.15																			
X.xx	±0.25																			
X.x	±0.35																			
<table border="1"> <tr> <td colspan="2">ANGULAR:</td> </tr> <tr> <td>X.xx°</td> <td>±1°</td> </tr> <tr> <td>X.x°</td> <td>±3°</td> </tr> <tr> <td>X.°</td> <td>±5°</td> </tr> </table>		ANGULAR:		X.xx°	±1°	X.x°	±3°	X.°	±5°											
ANGULAR:																				
X.xx°	±1°																			
X.x°	±3°																			
X.°	±5°																			