

REVISIONS					
REV.	ECN NO.	LOCATION	DESCRIPTION	DATE	DESIGN
A0	N/A		INITIAL RELEASE	/	/
A1	N/A		图面升级整理图面	2024.07.17	阿树

■SPECIFICATIONS

- Voltage rating:250V AC/DC
- Current rating:5A AC/DC
- Withstanding Voltage:1000V AC/minute
- Temperature range:-45°C+125°C
- Insulation resistance:≥1000MΩ
- Contact resistance:≤10mΩ
- After environmental testing: ≤20mΩ

PART NO.:

X3025 W R S-XX D-LP SW XX
① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

- ①Series No
②Category:W-Wafer
③Welding Board Angle:R-Straight 90°
④Welding Way: S-SMT
⑤Row No.Pin No:XX-02~12Pin
⑥Special NO:D-Solder Tabs
⑦Material:LP-LCP UL94V-0
⑧Planting Category:
SN-Bright tin plating
SW-Fog Tin plating
⑨Color:Blank-Natural Color

Poles	Dimensions (mm)		
	A	B	C
02	6.85	3.00	14.20
03	9.85	6.00	17.20
04	12.85	9.00	20.20
05	15.85	12.00	23.20
06	18.85	15.00	26.20
07	21.85	18.00	29.20
08	24.85	21.00	32.20
09	27.85	24.00	35.20
10	30.85	27.00	38.20
11	33.85	30.00	41.20
12	36.85	33.00	44.20

X3025WRS-XXD-LPG15	LCP UL 94V-0	Brass	Contact Area Gold:15u" Min.	Brass	Tin-Plated	X3025H
X3025WRS-XXD-LPSW	PA66 UL 94V-0		Tin Plating Fog			
PART NO	Material	Material(Pin)	Finish(Pin)	Material (Solder Tabs)	Finish (Solder Tabs)	Mates With XKB Housing

AuGLAR	±5°
X.	±0.40
X.x	±0.30
X.xx	±0.20
X.xxx	±0.15
UNSPECIFIED TOLERANCES	



DESIGN	阿树	VIEW:	
CHECKED		UNIT:	mm/in
APPROVED		SIZE:	A4

MODEL TYPE:	3.00mm Crimp Style Connectors
PART NO.:	X3025WRS-XXD-LPSW
DWG NO.:	

SCALE	PAGE	REVISION
N/A	1/1	A1