

1424837

https://www.phoenixcontact.com/us/products/1424837

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sleeve housing B32, for double locking latch, material: Die-cast aluminum, salt water resistant, cable outlets: 1, lateral, 1x M40, height: 94 mm, cable gland: none, Standard

### Your advantages

• Good shielding in the event of electromagnetic interference

#### Commercial data

Item number	1424837
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF56
Product key	BF7APB
Catalog page	Page 644 (C-2-2019)
GTIN	4055626382425
Weight per piece (including packing)	437.1 g
Weight per piece (excluding packing)	437.1 g
Customs tariff number	85389099
Country of origin	CN



1424837

https://www.phoenixcontact.com/us/products/1424837

#### Technical data

#### Product properties

Product type	Housing with locking latch
Housing type	Sleeve housing
Application	Standard
Туре	B32
No. of cable outlets	1
Type of the screw connection	1x M40
Туре	Tall design
Cable outlet	lateral
Pg screw connection	none

#### **Dimensions**

Dimensional drawing	3
Width	82.5 mm
Height	94 mm
Length	94 mm

#### Material specifications

Housing material	Die-cast aluminum, salt water resistant
Housing surface material	uncoated

#### Mechanical properties

#### Mechanical data

Type of the screw connection	1x M40
Locking type	Pin

#### Environmental and real-life conditions

#### Ambient conditions

Degree of protection	IP66
	IP67
Enclosure rating (NEMA)	4 (UL 50e)
	4X (UL 50e)
	12 (UL 50e)
Impact strength	IK09
Ambient temperature (operation)	-40 °C 125 °C





1424837

https://www.phoenixcontact.com/us/products/1424837

### Drawings

#### Dimensional drawing





Dimensional drawing



1424837

https://www.phoenixcontact.com/us/products/1424837

### **Approvals**

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1424837

DNV

Approval ID: TAE000037S



**cUL Recognized**Approval ID: E255026



**UL Recognized**Approval ID: E255026



**EAC** 

Approval ID: RU C-DE.BL08.B.00511

cULus Recognized



1424837

https://www.phoenixcontact.com/us/products/1424837

### Classifications

UNSPSC 21.0

#### **ECLASS**

ECLASS-11.0	27440202
ECLASS-12.0	27440202
ECLASS-13.0	27440202
ETIM	
ETIM 9.0	EC000437
UNSPSC	

31261500



1424837

https://www.phoenixcontact.com/us/products/1424837

### Environmental product compliance

EU	RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%



1424837

https://www.phoenixcontact.com/us/products/1424837

#### Accessories

#### HC-B32-HCWD-PLR-BK - Protective cover

1346555

https://www.phoenixcontact.com/us/products/1346555




Protective cover B32, with double locking latch, protective cover material: PC, height: 26.4 mm, seal: yes

#### US-EMLP (20X9) CUS - Plastic label

0830085

https://www.phoenixcontact.com/us/products/0830085







1424837

https://www.phoenixcontact.com/us/products/1424837

#### US-EMLP-HA (20X9) - Plastic label

0830989

https://www.phoenixcontact.com/us/products/0830989



Plastic label, Card, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: adhesive, lettering field size: 20 x 9 mm, Number of individual labels: 70

#### WP-G HF IP66 M40 BK - Screw connection

3240901

https://www.phoenixcontact.com/us/products/3240901



Cable gland, metric thread, IP66 protection, straight



1424837

https://www.phoenixcontact.com/us/products/1424837

#### WP-G HF IP69K M40 BK - Screw connection

3240887

https://www.phoenixcontact.com/us/products/3240887



Cable gland, metric thread, IP68/69k protection, straight

#### WP-GA HF IP66 M40 BK - Screw connection

3240929

https://www.phoenixcontact.com/us/products/3240929

Cable gland, metric thread, IP66 protection, angled





1424837

https://www.phoenixcontact.com/us/products/1424837

#### WP-GA HF IP69K M40 BK - Screw connection

3240915

https://www.phoenixcontact.com/us/products/3240915

Cable gland, metric thread, IP68/69k protection, angled



#### WP-GR HF IP66 M40 BK - Screw connection

3240957

https://www.phoenixcontact.com/us/products/3240957

Cable gland, metric thread, IP66 protection, with strain relief





1424837

https://www.phoenixcontact.com/us/products/1424837

#### WP-GR HF IP69K M40 BK - Screw connection

3240943

https://www.phoenixcontact.com/us/products/3240943



Cable gland, metric thread, IP68/69k protection, with strain relief

#### WP-G PP HF M40 - Screw connection

3241001

https://www.phoenixcontact.com/us/products/3241001



Cable gland made from PP with metric thread, IP65 protection



1424837

https://www.phoenixcontact.com/us/products/1424837

#### WP-GT PP HF M40 - Screw connection

3241015

https://www.phoenixcontact.com/us/products/3241015



Cable gland made from PP with metric thread, rotatable, IP54 protection

#### WP-G BRASS IP40 M40 - Screw connection

3241050

https://www.phoenixcontact.com/us/products/3241050



Cable gland made from brass with metric thread, IP40 protection



1424837

https://www.phoenixcontact.com/us/products/1424837

#### WP-GT BRASS M40 - Screw connection

3241036

https://www.phoenixcontact.com/us/products/3241036



Cable gland made from brass with metric thread, rotatable, IP40 protection

#### WP-G BRASS IP65 M40 - Screw connection

3241064

https://www.phoenixcontact.com/us/products/3241064



Cable gland made from brass with metric thread, IP65 protection

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com