

FO patch cable - FOC-LC:A-LC:A-GZ02/2 - 1400621

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Assembled FO cable, zip cord cable, multi-mode fiberglass 50/125 μ m, OM3, plug: LC/LC, degree of protection: IP20, for installation in cable ducts or control cabinets, length: 2 m

Your advantages

- Multi-mode patch cable for indoor installation
- Ideal for use in distributor systems and for connecting termination devices
- ✓ All components satisfy UL 94, V0
- 2.8 mm single elements made from halogen-free and flame-retardant material

- Connector with UPC polishing for optimum attenuation values
- Insertion loss ≤ 0.5 dB
- ✓ Return loss ≥ 35 dB
- Temperature fluctuation test according to IEC 61300-2-1
- ✓ Vibration test according to IEC 61300-2-1
- ☑ Tensile strength of the cable connection according to IEC 61300-2-5



Key Commercial Data

Packing unit	1 pc
GTIN	4 046356 734769
GTIN	4046356734769

Technical data

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e



FO patch cable - FOC-LC:A-LC:A-GZ02/2 - 1400621

Technical data

Environmental Product Compliance

		No hazardous substances above threshold values	
Approvals			
Approvals			
Approvals			
UL Listed / EAC			
Ex Approvals			
Approval details			
UL Listed	UL	http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	E308814-20070105
EAC	EAC		B.00767

Phoenix Contact 2019 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com