

1705561

https://www.phoenixcontact.com/us/products/1705561

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Seal, Range of articles: SUNCLIX

Product description

Flat gasket for photovoltaic connector

Commercial data

Item number	1705561
Packing unit	1,000 pc
Minimum order quantity	1,000 pc
Product key	ABLBZC
Catalog page	Page 420 (C-2-2013)
GTIN	4046356772723
Weight per piece (including packing)	0.117 g
Weight per piece (excluding packing)	0.113 g
Country of origin	DE

1705561

https://www.phoenixcontact.com/us/products/1705561



Technical data

Notes

Safety note

Safety note

- WARNING: Commission properly functioning products only.
 The products must be regularly inspected for damage.
 Decommission defective products immediately. Replace damaged products. Repairs are not possible.
- WARNING: Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product.

WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property.

- The products are suitable for applications in plant, controller, and electrical device engineering.
- Assembled products may not be manipulated or improperly opened.
- Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at phoenixcontact.com/products).
- When using the product in direct connection with third-party manufacturers, the user is responsible.
- For operating voltages > 50 V AC, conductive connector housings must be grounded
- Ensure that the protective or functional ground has been properly connected.
- Observe the corresponding technical data. You will find information:
- o On the product
- o On the packing label
- o In the supplied documentation
- o Online at phoenixcontact.com/products under the product
- The installation notes/Design In documents online on the download page at phoenixcontact.com/products must be observed for this product.
- Use a protective cap to protect connectors that are not in use. The suitable accessories are available online in the accessory section of the product at phoenixcontact.com/products
- The connector warms up in normal operation. Depending on the ambient conditions, the surface of the connector can continue to warm up. In this case, the user is responsible for posting warnings (e.g. DIN EN ISO 13732-1:2008-12).
- Operate the connector only when it is fully plugged in and interlocked.
- Ensure that when laying the cable, the tensile load on the connectors does not exceed the upper limit specified in the standards.



1705561

https://www.phoenixcontact.com/us/products/1705561

Observe the minimum bending radius of the cable. Lay the able without twisting it. anel feed-through
anel feed-through
anel feed-through
UNCLIX
7 mm
7 mm
.8 mm
1



1705561

https://www.phoenixcontact.com/us/products/1705561

Classifications

UNSPSC 21.0

ECLASS

ECLASS	i-11.0	27371392
ECLASS	i-12.0	27371392
ECLASS	-13.0	27371392
ETIM		
ETIM 9.0		EC002498
UNSPSC		

39121100



https://www.phoenixcontact.com/us/products/1705561



Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com