

zQSFP+/QSFP28

TE Internal #: 2289129-2

zQSFP+, Cage Assembly with Integrated Connector, .8mm [.032in]

Centerline, Signal, Operating Temperature Range -40 – 85 °C [-40 –

185 °F]

View on TE.com >



Connectors > Pluggable IO Connectors & Cages











Pluggable I/O Product Type: Cage Assembly with Integrated Connector

Centerline (Pitch): .8 mm [.032 in]

Sealable: No

Circuit Application: Signal

Operating Temperature Range: -40 - 85 °C [-40 - 185 °F]

Features

Product Type Features

Cage Type	Stacked
Pluggable I/O Product Type	Cage Assembly with Integrated Connector
Sealable	No
Form Factor	zQSFP+
Configuration Features	
Number of Rear EONs per Port Column	3
Number of Positions	152
Number of Ports	4
Port Matrix Configuration	2 x 2
Electrical Characteristics	

Contact Features

Data Rate (Max)

Contact Mating Area Plating Material Thickness	.76 μm[30 μin]
Contact Mating Area Plating Material	Gold

25 Gb/s



Contact Underplating Material	Tin
PCB Contact Termination Area Plating Material	Gold
Contact Current Rating (Max)	.5 A

Termination Features

Termination Post & Tail Length	2 mm[.079 in]
Termination Method to PCB	Through Hole - Press-Fit

Housing Features

Cage Material	Nickel Silver
Centerline (Pitch)	.8 mm[.032 in]

Dimensions

PCB Thickness (Recommended)	1.57 mm[.062 in]	

Usage Conditions

Operating Temperature Range -40 – 85 °C[-40 – 185 °F]	Operating Temperature Range	-40 - 85 °C[-40 - 185 °F]	
---	-----------------------------	---------------------------	--

Operation/Application

Pluggable I/O Applications	SFP+ Stacked Belly-to-Belly
Heat Sink Compatible	No
Circuit Application	Signal

Industry Standards

UL Flammability Rating	UL 94V-0	

Packaging Features

Other

Included Lightpipe	Yes
EMI Containment Feature Type	Internal/External EMI Springs

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241)



Candidate List Declared Against: JUNE
2024 (241)
Does not contain REACH SVHC

Halogen Content	Not Low Halogen - contains Br or Cl > 900
	ppm.

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


Compatible Parts





Also in the Series | zQSFP+/QSFP28







Customers Also Bought

zQSFP+, Cage Assembly with Integrated Connector, .8mm [.032in] Centerline, Signal, Operating Temperature Range -40 – 85 °C [-40 – 185 °F]






TE Part #3-5353652-6 .5FHP08H,440,B,GIG,08/Sn,HT,NSYes



TE Part #2-1926739-5
AssyMinipak Hdl25s10pRARecptSc



TE Part #8-6450130-5 MBXL R/A HDR 1P+16S+1P





TE Part #3-2339978-2 SFP56 STACKED 2X4 RECEPTACLE ASSEMBLY



TE Part #1643903-3 Crown Clip Senior II, Ag Plating

TE Part #1-2333126-2 CAGE ASSY, QSFP -DD 1X1, STANDARD, 4LP TE Part #2-2333126-2 CAGE ASSY, QSFP-DD 1X1, STANDARD, 4LP

TE Part #2016623-6
RF CA,1.0-2.3 BULKHEAD TO UMCC
GEN1,1.37

TE Part #2016623-7 RF CA,1.0-2.3 BKD TO UMCC GEN1, 1.37 BK

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2289129-2_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2289129-2_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2289129-2_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages

QSFP28/56 and zQSFP+ Interconnects

English

Product Specifications

zQSFP+, Cage Assembly with Integrated Connector, .8mm [.032in] Centerline, Signal, Operating Temperature Range -40 – 85 °C [-40 – 185 °F]



Application Specification

English